



PROBLEM SOLVER

Baseboard Cleaner

FEATURES

- Jelled cleaner designed for removing wax and soil build up on floors
- Stability on vertical surfaces
- Will not drip or run and extends contact time
- Removes wax and buildup from many surface types as well as baseboards

APPLICATIONS

- Floors
- Baseboards
- Ceramic
- Other hard to clean surfaces

DIRECTIONS

Shake well before using. Hold can upside down and spray onto surface (thin even coat). Wait 3-5 minutes, wet scrub, and rinse with warm water.

HANDLING

Wear protective gloves and eye protection. Rinse cautiously with water for several minutes if skin contact occurs. Consult a doctor under certain circumstances. Please refer to the label or SDS for first aid instructions.

STORAGE

Do not pierce or burn, even after use. Keep away from heat/sparks/open flames/hot surfaces. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Keep out of reach of children

DISPOSAL

Dispose of chemical/container according to local/regional/national/international waste disposal regulations.



PROPERTIES

Appearance / Physical State	Aerosol
Color	Light, tan
Odor	Pleasant
Boiling Point / Range	212°F (100°C)
Vapor Pressure	60 psig @ 21°C (70°F)
Propellant	Liquefied Petroleum Gas (LPG)
VOC Content	21.61%
Evaporation Rate	Not applicable
Vapor density	> 1 (Air=1)
Density	1.06 g/cm (8.846 lbs/gal) @ 20°C (68°F)
pH Value	>13
Water Solubility	Miscible.
Flammability	Flammable

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
23920	18 oz / 510 g	aerosol	12	18 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved