Dykem® Brite-Mark® - Pink

ITW PRO BRANDS. -KS

Part Number: **84009**
Version No: **2.7**
Safety Data Sheet according to OSHA HazCom Standard (2024) requirements

Initial Date: **04/11/2023**
Revision Date: **06/02/2026**
Print Date: **06/02/2026**
S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Dykem® Brite-Mark® - Pink
Proper shipping name	PAINT
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	For Industrial Use Only Use according to manufacturer's directions.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	**ITW PRO BRANDS. -KS**
Address	805 E. Old 56 Highway Olathe, KS 66061 United States
Telephone	770-243-8800
Fax	Not Available
Website	www.itwprobrands.com
Email	Customerservice@itwprobrands.com

Emergency phone number

Association / Organisation	**Dykem/Dymon/Scrubs = Call InfoTrac For_LPS & Other Brands = Call Chemtrec**
Emergency telephone number(s)	**1-800-535-5053 (Infotrac Inside US) 1-800-424-9300 (Chemtrec Inside US)**
Other emergency telephone number(s)	**1-352-323-3500 (Infotrac Ouside US) +001 703-527-3887 (Chemtrec Outside US)**

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

Classification	Flammable Liquids Category 2, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3

Label elements

Hazard pictogram(s)	
Signal word	**Danger**

Hazard statement(s)

H225	Highly flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.

Page 1 continued...

P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist/vapours/spray.
P280	Wear protective gloves and protective clothing.

Precautionary statement(s) Response

P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
123-86-4	15-40	n-butyl acetate
108-65-6	5-10	propylene glycol monomethyl ether acetate, alpha-isomer*****
64742-49-0	1-5	NAPHTHA, HYDROTREATED LIGHT (R)
13463-67-7	15-40	TITANIUM DIOXIDE(R)

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: ▸ Wash out immediately with water. ▸ If irritation continues, seek medical attention. ▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ▸ Immediately remove all contaminated clothing, including footwear. ▸ Flush skin and hair with running water (and soap if available). ▸ Seek medical attention in event of irritation.
Inhalation	▸ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▸ Other measures are usually unnecessary.
Ingestion	▸ Immediately give a glass of water. ▸ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▸ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting	▸ Alert Fire Brigade and tell them location and nature of hazard. ▸ May be violently or explosively reactive. ▸ Wear breathing apparatus plus protective gloves in the event of a fire.

Continued...

	▸ Prevent, by any means available, spillage from entering drains or water course. ▸ Consider evacuation (or protect in place). ▸ Fight fire from a safe distance, with adequate cover. ▸ If safe, switch off electrical equipment until vapour fire hazard removed. ▸ Use water delivered as a fine spray to control the fire and cool adjacent area. ▸ Avoid spraying water onto liquid pools. ▸ **Do not** approach containers suspected to be hot. ▸ Cool fire exposed containers with water spray from a protected location. ▸ If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	▸ Liquid and vapour are highly flammable. ▸ Severe fire hazard when exposed to heat, flame and/or oxidisers. ▸ Vapour may travel a considerable distance to source of ignition. ▸ Heating may cause expansion or decomposition leading to violent rupture of containers. ▸ On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: ▸ carbon dioxide (CO_2) ▸ other pyrolysis products typical of burning organic material.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	▸ Remove all ignition sources. ▸ Clean up all spills immediately. ▸ Avoid breathing vapours and contact with skin and eyes. ▸ Control personal contact with the substance, by using protective equipment. ▸ Contain and absorb small quantities with vermiculite or other absorbent material. ▸ Wipe up. ▸ Collect residues in a flammable waste container.
Major Spills	▸ Clear area of personnel and move upwind. ▸ Alert Fire Brigade and tell them location and nature of hazard. ▸ May be violently or explosively reactive. ▸ Wear breathing apparatus plus protective gloves. ▸ Prevent, by any means available, spillage from entering drains or water course. ▸ Consider evacuation (or protect in place). ▸ No smoking, naked lights or ignition sources. ▸ Increase ventilation. ▸ Stop leak if safe to do so. ▸ Water spray or fog may be used to disperse /absorb vapour. ▸ Contain spill with sand, earth or vermiculite. ▸ Use only spark-free shovels and explosion proof equipment. ▸ Collect recoverable product into labelled containers for recycling. ▸ Absorb remaining product with sand, earth or vermiculite. ▸ Collect solid residues and seal in labelled drums for disposal. ▸ Wash area and prevent runoff into drains. ▸ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▸ Avoid skin contact, including inhalation. ▸ Wear protective clothing when risk of exposure occurs. ▸ Use in a well-ventilated area. ▸ Prevent concentration in hollows and sumps. ▸ **DO NOT** enter confined spaces until atmosphere has been checked. ▸ Avoid smoking, naked lights, heat or ignition sources. ▸ When handling, **DO NOT** eat, drink or smoke. ▸ Use spark-free tools when handling. ▸ Avoid contact with incompatible materials. ▸ Keep containers securely sealed. ▸ Avoid physical damage to containers. ▸ Always wash hands with soap and water after handling. ▸ Work clothes should be laundered separately. ▸ Use good occupational work practice. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS. ▸ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
Other information	▸ Store in original containers in approved flame-proof area. ▸ No smoking, naked lights, heat or ignition sources. ▸ **DO NOT** store in pits, depression, basement or areas where vapours may be trapped. ▸ Keep containers securely sealed. ▸ Store away from incompatible materials in a cool, dry well ventilated area. ▸ Protect containers against physical damage and check regularly for leaks. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	▸ Packing as supplied by manufacturer. ▸ Plastic containers may only be used if approved for flammable liquid. ▸ Check that containers are clearly labelled and free from leaks.

Continued...

Storage incompatibility	▸ Avoid reaction with oxidising agents



+	x	+	x	+	+	+

X — *Must not be stored together*
0 — *May be stored together with specific preventions*
\+ — *May be stored together*

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	n-butyl acetate	n-Butyl-acetate	150 ppm / 710 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	n-butyl acetate	n-Butyl acetate	150 ppm / 710 mg/m3	950 mg/m3 / 200 ppm	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	TITANIUM DIOXIDE(R)	Titanium dioxide - Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	TITANIUM DIOXIDE(R)	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	TITANIUM DIOXIDE(R)	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	TITANIUM DIOXIDE(R)	Titanium dioxide	Not Available	Not Available	Not Available	Ca; See Appendix A - NIOSH Potential Occupational Carcinogens

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
n-butyl acetate	Not Available	Not Available	Not Available
TITANIUM DIOXIDE(R)	30 mg/m3	330 mg/m3	2,000 mg/m3
propylene glycol monomethyl ether acetate, alpha-isomer*****	Not Available	Not Available	Not Available
NAPHTHA, HYDROTREATED LIGHT (R)	1,000 mg/m3	11,000 mg/m3	66,000 mg/m3

Ingredient	Original IDLH	Revised IDLH
n-butyl acetate	1,700 ppm	Not Available
TITANIUM DIOXIDE(R)	5,000 mg/m3	Not Available
propylene glycol monomethyl ether acetate, alpha-isomer*****	Not Available	Not Available
NAPHTHA, HYDROTREATED LIGHT (R)	Not Available	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
The basic types of engineering controls are:
Process controls which involve changing the way a job activity or process is done to reduce the risk.
Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
Employers may need to use multiple types of controls to prevent employee overexposure.
For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.
Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)

Continued...

	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) — 1-2.5 m/s (200-500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.
· Adequate ventilation is typically taken to be that which limits the average concentration to no more than 25% of the LEL within the building, room or enclosure containing the dangerous substance.
· Ventilation for plant and machinery is normally considered adequate if it limits the average concentration of any dangerous substance that might potentially be present to no more than 25% of the LEL. However, an increase up to a maximum 50% LEL can be acceptable where additional safeguards are provided to prevent the formation of a hazardous explosive atmosphere. For example, gas detectors linked to emergency shutdown of the process might be used together with maintaining or increasing the exhaust ventilation on solvent evaporating ovens and gas turbine enclosures.
· Temporary exhaust ventilation systems may be provided for non-routine higher-risk activities, such as cleaning, repair or maintenance in tanks or other confined spaces or in an emergency after a release. The work procedures for such activities should be carefully considered.. The atmosphere should be continuously monitored to ensure that ventilation is adequate and the area remains safe. Where workers will enter the space, the ventilation should ensure that the concentration of the dangerous substance does not exceed 10% of the LEL (irrespective of the provision of suitable breathing apparatus)

Individual protection measures, such as personal protective equipment	
Eye and face protection	‣ Safety glasses with side shields. ‣ Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent] ‣ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection	See Hand protection below
Hands/feet protection	‣ Wear chemical protective gloves, e.g. PVC. ‣ Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	‣ Overalls. ‣ PVC Apron. ‣ PVC protective suit may be required if exposure severe. ‣ Eyewash unit. ‣ Ensure there is ready access to a safety shower.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Pink

Physical state	Liquid	**Relative density (Water = 1)**	Not Available
Odour	Characteristic	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Applicable
pH (as supplied)	Not Available	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (cSt)**	Not Available
Initial boiling point and boiling range (°C)	118	**Molecular weight (g/mol)**	Not Available
Flash point (°C)	14	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	HIGHLY FLAMMABLE.	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	<13	**Surface Tension (dyn/cm or mN/m)**	Not Available
Lower Explosive Limit (%)	0.9	**Volatile Component (%vol)**	Not Available
Vapour pressure (kPa)	Not Available	**Gas group**	Not Available
Solubility in water	Immiscible	**pH as a solution (1%)**	Not Available
Vapour density (Air = 1)	Not Available	**VOC %**	47%
Heat of Combustion (kJ/g)	Not Available	**Ignition Distance (cm)**	Not Available

Continued...

Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available
Nanoform Solubility	Not Available	**Nanoform Particle Characteristics**	Not Available
Particle Size	Not Available		

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▸ Unstable in the presence of incompatible materials. ▸ Product is considered stable. ▸ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	There is sufficient evidence to classify this material as toxic to specific organs through single exposure
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.
Ingestion	The material has **NOT** been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.

Dykem® Brite-Mark® - Pink

TOXICITY	IRRITATION
Not Available	Not Available

n-butyl acetate

TOXICITY	IRRITATION
Dermal (rabbit) LD50: 3200 mg/kg*[2]	Eye (Human): 300ppm
Inhalation (Human) TCLo: 200 ppm[2]	Eye (Rodent - rabbit): 100mg - Moderate
Inhalation (Human) TCLo: 200 ppm/4h[2]	Eye: no adverse effect observed (not irritating)[1]
Inhalation (Rat) LC50: 2000 ppm/4H[2]	Skin (Rodent - rabbit): 500mg/24H - Moderate
Inhalation (Rat) LC50: 390 ppm/4h[2]	Skin: no adverse effect observed (not irritating)[1]
Intraperitoneal (Guinea pig) LD: 1500 mg/kg[2]	
Intraperitoneal (Mouse) LD50: 1230 mg/kg[2]	
Oral (Guinea) LD50; 4700 mg/kg[2]	
Oral (Rabbit) LD50: 3200 mg/kg[2]	
Oral (Rat) LD50: 10768 mg/kg[2]	
Oral (Rat) LD50: 13100 mg/kg[2]	

Continued...

TITANIUM DIOXIDE(R)	

TOXICITY	IRRITATION
dermal (hamster) LD50: >=10000 mg/kg[2]	Eye: no adverse effect observed (not irritating)[1]
Inhalation (Rat) LC50: >2.28 mg/l4h[1]	Skin (Human): 300ug/3D (intermittent) - Mild
Oral (Rat) LD50: >=2000 mg/kg[1]	Skin: no adverse effect observed (not irritating)[1]

propylene glycol monomethyl ether acetate, alpha-isomer***

TOXICITY	IRRITATION
Dermal (rabbit) LD50: >5000 mg/kg[2]	Eye: no adverse effect observed (not irritating)[1]
Dermal (rabbit) LD50: >5000 mg/kg*[2]	Skin: no adverse effect observed (not irritating)[1]
Inhalation (Rat)LC0: >3100 mg/m3/4h *[2]	
Inhalation (Rat)LC50: 4345 ppm/6h[2]	
Intraperitoneal (Mouse) LD50: 750 mg/kg[2]	
Oral (Rat) LD50: 8532 mg/kg[2]	
Oral (Rat, adult male) LD50: >10000 mg/kg *[2]	

NAPHTHA, HYDROTREATED LIGHT (R)

TOXICITY	IRRITATION
dermal (rat) LD50: 3.35 mg/kg[2]	Eye: no adverse effect observed (not irritating)[1]
Inhalation (Rat) LC50: 0.26 mg/L4h[2]	Skin: adverse effect observed (irritating)[1]
Oral (Rat) LD50: 16.75 mg/kg[2]	

Legend: ***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✗	**Reproductivity**	✗
Serious Eye Damage/Irritation	✗	**STOT - Single Exposure**	✓
Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✗

Legend: ✗ ***– Data either not available or does not fill the criteria for classification***
✓ ***– Data available to make classification***

SECTION 12 Ecological information

Toxicity

Dykem® Brite-Mark® - Pink

Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

n-butyl acetate

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	72h	Algae or other aquatic plants	246mg/l	2
EC50	48h	Crustacea	32mg/l	1
EC50(ECx)	96h	Fish	18mg/l	2
LC50	96h	Fish	17-19mg/L	4

TITANIUM DIOXIDE(R)

Endpoint	Test Duration (hr)	Species	Value	Source
BCF	1008h	Fish	<1.1-9.6	7
EC50	72h	Algae or other aquatic plants	3.75-7.58mg/l	4
EC50	48h	Crustacea	1.9mg/l	2
NOEC(ECx)	672h	Fish	>=0.004mg/L	2
EC50	96h	Algae or other aquatic plants	179.05mg/l	2
LC50	96h	Fish	1.85-3.06mg/l	4

propylene glycol monomethyl ether acetate, alpha-isomer***

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	96h	Algae or other aquatic plants	>1000mg/l	2
LC50	96h	Fish	100-180mg/l	2
EC50	72h	Algae or other aquatic plants	>1000mg/l	2
EC50	48h	Crustacea	373mg/l	2
NOEC(ECx)	336h	Fish	47.5mg/l	2

Continued...

NAPHTHA, HYDROTREATED LIGHT (R)	

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	48h	Crustacea	0.64mg/l	2
EC50	96h	Algae or other aquatic plants	64mg/l	2
NOEC(ECx)	504h	Crustacea	0.17mg/l	2
LC50	96h	Fish	0.11mg/l	2

Legend:	***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data***

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
n-butyl acetate	LOW	LOW
TITANIUM DIOXIDE(R)	HIGH	HIGH
propylene glycol monomethyl ether acetate, alpha-isomer*****	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
n-butyl acetate	LOW (BCF = 14)
TITANIUM DIOXIDE(R)	LOW (BCF = 10)
propylene glycol monomethyl ether acetate, alpha-isomer*****	LOW (LogKOW = 0.56)

Mobility in soil

Ingredient	Mobility
n-butyl acetate	LOW (Log KOC = 20.86)
TITANIUM DIOXIDE(R)	LOW (Log KOC = 23.74)
propylene glycol monomethyl ether acetate, alpha-isomer*****	HIGH (Log KOC = 1.838)

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	▸ Recycle wherever possible. ▸ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. ▸ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material). ▸ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	NO

Shipping container, transport vehicle placarding, and labeling may vary from the below information. This depends on the quantity shipped, the applicability of excepted quantity requirements, limited quantity requirements, and/or special provisions according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

Land transport (DOT)

14.1. **UN number or ID number**	1263
14.2. **UN proper shipping name**	PAINT
14.3. **Transport hazard class(es)**	Class: 3 Subsidiary Hazard: Not Applicable
14.4. **Packing group**	II
14.5. **Environmental hazard**	Not Applicable

Continued...

14.6. **Special precautions for user**	Hazard Label: 3 Special provisions: 149, 367, B52, B131, IB2, T4, TP1, TP8, TP28

Air transport (ICAO-IATA / DGR)

14.1. **UN number**	1263
14.2. **UN proper shipping name**	PAINT
14.3. **Transport hazard class(es)**	ICAO/IATA Class: 3 ICAO / IATA Subsidiary Hazard: Not Applicable ERG Code: 3L
14.4. **Packing group**	II
14.5. **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	Special provisions: A3 A72 A192 Cargo Only Packing Instructions: 364 Cargo Only Maximum Qty / Pack: 60 L Passenger and Cargo Packing Instructions: 353 Passenger and Cargo Maximum Qty / Pack: 5 L Passenger and Cargo Limited Quantity Packing Instructions: Y341 Passenger and Cargo Limited Maximum Qty / Pack: 1 L

Sea transport (IMDG-Code / GGVSee)

14.1. **UN number**	1263
14.2. **UN proper shipping name**	PAINT
14.3. **Transport hazard class(es)**	IMDG Class: 3 IMDG Subsidiary Hazard: Not Applicable
14.4. **Packing group**	II
14.5 **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	EMS Number: F-E, S-E Special provisions: 163 367 Limited Quantities: 5 L

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
n-butyl acetate	Not Applicable
TITANIUM DIOXIDE(R)	Not Applicable
propylene glycol monomethyl ether acetate, alpha-isomer*****	Not Applicable
NAPHTHA, HYDROTREATED LIGHT (R)	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
n-butyl acetate	Not Applicable
TITANIUM DIOXIDE(R)	Not Applicable
propylene glycol monomethyl ether acetate, alpha-isomer*****	Not Applicable
NAPHTHA, HYDROTREATED LIGHT (R)	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

n-butyl acetate is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Flammables
US - New Jersey Right to Know Hazardous Substances
US - Pennsylvania - Hazardous Substance List

Continued...

US CWA (Clean Water Act) - List of Hazardous Substances
US DOE Temporary Emergency Exposure Limits (TEELs)
US New York City Community Right-to-Know: List of Hazardous Substances
US NIOSH Recommended Exposure Limits (RELs)
US OSHA Permissible Exposure Limits (PELs) Table Z-1
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US TSCA Section 4/12 (b) - Sunset Dates/Status

TITANIUM DIOXIDE(R) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans
International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)
US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5
US - California Proposition 65 - Carcinogens
US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List
US - Massachusetts - Right To Know Listed Chemicals
US - New Jersey Right to Know Hazardous Substances
US - Pennsylvania - Hazardous Substance List
US DOE Temporary Emergency Exposure Limits (TEELs)
US New York City Community Right-to-Know: List of Hazardous Substances
US NIOSH Recommended Exposure Limits (RELs)
US OSHA Permissible Exposure Limits (PELs) Table Z-1
US OSHA Permissible Exposure Limits (PELs) Table Z-3
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

propylene glycol monomethyl ether acetate, alpha-isomer*** is found on the following regulatory lists**

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants
US - Pennsylvania - Hazardous Substance List
US AIHA Workplace Environmental Exposure Levels (WEELs)
US DOE Temporary Emergency Exposure Limits (TEELs)
US New York City Community Right-to-Know: List of Hazardous Substances
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL)

NAPHTHA, HYDROTREATED LIGHT (R) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic
US DOE Temporary Emergency Exposure Limits (TEELs)
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Additional Regulatory Information

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

Continued...

Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
n-butyl acetate	5000	2270

US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372)

This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know-Act of 1986 (40 CFR 372):

CAS No	%[weight]	Name
1344-28-1.	2.225	aluminium oxide
108-88-3	0.02092	TOLUENE(R)
100-41-4	0.02092	ethylbenzene
91-20-3	0.02092	naphthalene
71-43-2	0.02092	benzene

This information must be included in all SDSs that are copied and distributed for this material.

Additional Federal Regulatory Information

Not Applicable

State Regulations

US. California Proposition 65

WARNING: This product can expose you to chemicals including **TITANIUM DIOXIDE(R), ethylbenzene, naphthalene, benzene**, which are known to the State of California to cause cancer, and **TOLUENE(R), benzene**, which are known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Additional State Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (n-butyl acetate; TITANIUM DIOXIDE(R); propylene glycol monomethyl ether acetate, alpha-isomer*****; NAPHTHA, HYDROTREATED LIGHT (R))
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (NAPHTHA, HYDROTREATED LIGHT (R))
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	No (n-butyl acetate; TITANIUM DIOXIDE(R); propylene glycol monomethyl ether acetate, alpha-isomer*****; NAPHTHA, HYDROTREATED LIGHT (R))
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 Other information

Revision Date	06/02/2026
Initial Date	04/11/2023

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Powered by AuthorITe, from Chemwatch.

end of SDS