

LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)

ITW Permatest

Part Number: 07220, 97220

Version No: 1.8

Safety Data Sheet according to WHMIS 2023 requirements

Initial Date: 20/09/2025

Revision Date: 17/10/2025

Print Date: 21/10/2025

S.GHS.CAN.EN

SECTION 1 Identification

Product Identifier

Product name	LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)
Proper shipping name	AEROSOLS
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	For Industrial Use Only Use according to manufacturer's directions.
--------------------------	--

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ITW Permatest	ITW Pro Brands. -GA
Address	2360 Bristol Circle, Ste 101 Oakville, ON L6H 6M5 Canada	4647 Hugh Howell Rd. Tucker, GA United States
Telephone	1-800-241-8334	770-243-8800
Fax	1-800-543-1563	Not Available
Website	www.itwprobrands.com	www.itwprobrands.com
Email	lpssds@itwprobrands.com	lpssds@itwprobrands.com

Emergency phone number

Association / Organisation	Dykem/Dymon/Scrubs = Call InfoTrac For _LPS & Other Brands = Call Chemtrec	Dykem/Dymon/Scrubs = Call InfoTrac For _LPS & Other Brands = Call Chemtrec
Emergency telephone number(s)	1-352-323-3500 (Infotrac) +001 703-527-3887 (Chemtrec)	1-800-535-5053 (InfoTrac Inside US) 1-800-424-9300 (Chemtrec Inside US)
Other emergency telephone number(s)	1-800-424-9300 (inside U.S.)	1-352-323-3500 (Infotrac Outside US) +001 703-527-3887 (Chemtrec Outside US)

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

Classification	Aerosols, Hazard Category 3, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2A, Acute Toxicity (Inhalation) Category 4, Specific Target Organ Toxicity - Single Exposure Category 3
----------------	---

Label elements

Hazard pictogram(s)	
---------------------	---

Signal word	Warning
-------------	---------

Hazard statement(s)

H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335+H336	May cause respiratory irritation or drowsiness or dizziness.

Physical hazard(s) not otherwise classified

NOTE: This aerosol is non-flammable per the Enclosed Space Ignition Test

Precautionary statement(s) Prevention

LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing gas.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P264	Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
156-60-5	45-70	TRANS-DICHLOROETHYLENE(R)
406-78-0	15-40	1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*
124-38-9	1-5	carbon dioxide

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If aerosols come in contact with the eyes: ▶ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. Seek medical attention in the event of irritation.
Skin Contact	If solids or aerosol mists are deposited upon the skin: ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in the event of irritation.
Inhalation	If aerosols, fumes or combustion products are inhaled: ▶ Remove to fresh air. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Seek medical attention in the event of irritation.
Ingestion	Not considered a normal route of entry.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

SMALL FIRE: Use extinguishing agent suitable for type of surrounding fire.

LARGE FIRE: Cool cylinder.

DO NOT direct water at source of leak or venting safety devices as icing may occur.

SMALL FIRE:

- ▶ Water spray, dry chemical or CO2

LARGE FIRE:

LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)

- ▶ Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility

- ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting	GENERAL ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus and protective gloves. ▶ Fight fire from a safe distance, with adequate cover. ▶ Use water delivered as a fine spray to control fire and cool adjacent area. ▶ DO NOT approach cylinders suspected to be hot. ▶ Cool fire exposed cylinders with water spray from a protected location. ▶ If safe to do so, remove cylinders from path of fire. SPECIAL REQUIREMENTS: ▶ Excessive pressures may develop in a gas cylinder exposed in a fire; this may result in explosion. ▶ Cylinders with pressure relief devices may release their contents as a result of fire and the released gas may constitute a further source of hazard for the fire-fighter. ▶ Cylinders without pressure-relief valves have no provision for controlled release and are therefore more likely to explode if exposed to fire. FIRE FIGHTING REQUIREMENTS: The need for proximity, entry and special protective clothing should be determined for each incident, by a competent fire-fighting safety professional.
Fire/Explosion Hazard	▶ Non combustible. ▶ Not considered to be a significant fire risk. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ Aerosol cans may explode on exposure to naked flames. ▶ Rupturing containers may rocket and scatter burning materials. ▶ Hazards may not be restricted to pressure effects. ▶ May emit acrid, poisonous or corrosive fumes. ▶ Decomposes on heating and may emit toxic fumes of carbon monoxide (CO). Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Wear protective clothing, impervious gloves and safety glasses. ▶ Shut off all possible sources of ignition and increase ventilation. ▶ Wipe up. ▶ If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. ▶ Undamaged cans should be gathered and stowed safely.
Major Spills	▶ DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve. ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water courses ▶ No smoking, naked lights or ignition sources. ▶ Increase ventilation. ▶ Stop leak if safe to do so. ▶ Water spray or fog may be used to disperse / absorb vapour. ▶ Absorb or cover spill with sand, earth, inert materials or vermiculite. ▶ If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. ▶ Undamaged cans should be gathered and stowed safely. ▶ Collect residues and seal in labelled drums for disposal.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ Avoid smoking, naked lights or ignition sources. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. ▶ DO NOT incinerate or puncture aerosol cans. ▶ DO NOT spray directly on humans, exposed food or food utensils. ▶ Avoid physical damage to containers.
---------------	---

Continued...

LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)

	▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can

Conditions for safe storage, including any incompatibilities

Suitable container	▶ Aerosol dispenser. ▶ Check that containers are clearly labelled.
Storage incompatibility	▶ Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances ▶ Avoid reaction with oxidising agents



X — Must not be stored together

O — May be stored together with specific precautions

+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	TRANS-DICHLOROETHYLENE(R)	1,2-Dichloroethylene, all isomers	200 ppm	250 ppm	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	TRANS-DICHLOROETHYLENE(R)	Not Available	200 ppm	Not Available	Not Available	TLV® Basis: CNS impair; eye irr
Canada - Prince Edward Island Occupational Exposure Limits	TRANS-DICHLOROETHYLENE(R)	1, 2-Dichloroethylene, all isomers	200 ppm	Not Available	Not Available	TLV® Basis: CNS impair; eye irr
Canada - British Columbia Occupational Exposure Limits	TRANS-DICHLOROETHYLENE(R)	1,2-Dichloroethylene, all isomers	200 ppm	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	TRANS-DICHLOROETHYLENE(R)	Acetylene dichloride (1,2-Dichloroethylene)	200 ppm / 793 mg/m3	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	TRANS-DICHLOROETHYLENE(R)	1,2-Dichloroethylene, all isomers (Acetylene dichloride)	200 ppm / 793 mg/m3	Not Available	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits	TRANS-DICHLOROETHYLENE(R)	1,2-Dichloroethylene, all isomers	200 ppm	250 ppm	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure LimitsCanada	TRANS-DICHLOROETHYLENE(R)	1,2-Dichloroethylene, trans-isomer	200 ppm	Not Available	Not Available	TLV Basis: central nervous system impairment; eye irritation
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	carbon dioxide	Carbon dioxide	5,000 ppm / 9,000 mg/m3	27,000 mg/m3 / 15,000 ppm	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	carbon dioxide	Carbon dioxide	5000 ppm	30,000 ppm	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	carbon dioxide	Not Available	5000 ppm	30000 ppm	Not Available	TLV® Basis: Asphyxia
Canada - Prince Edward Island Occupational Exposure Limits	carbon dioxide	Carbon dioxide	5000 ppm	30000 ppm	Not Available	TLV® Basis: Asphyxia
Canada - British Columbia Occupational Exposure Limits	carbon dioxide	Carbon dioxide	5000 ppm	15,000 ppm	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	carbon dioxide	Carbon dioxide	5000 ppm / 9000 mg/m3	54,000 mg/m3 / 30,000 ppm	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits	carbon dioxide	Carbon dioxide	5000 ppm	30,000 ppm	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	carbon dioxide	Carbon dioxide	5000 ppm / 9000 mg/m3	54000 mg/m3 / 30000 ppm	Not Available	Not Available

Continued...

LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Nova Scotia Occupational Exposure LimitsCanada	carbon dioxide	Carbon dioxide	5000 ppm	30000 ppm	Not Available	TLV Basis: asphyxia; 19.5% minimum oxygen content by volume under normal atmospheric pressure.
Ingredient	Original IDLH		Revised IDLH			
TRANS-DICHLOROETHYLENE(R)	Not Available		Not Available			
1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*	Not Available		Not Available			
carbon dioxide	40,000 ppm		Not Available			

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.	
	General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.	
	Type of Contaminant:	Speed:
	aerosols, (released at low velocity into zone of active generation)	0.5-1 m/s
	direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)
	Within each range the appropriate value depends on:	
	Lower end of the range	Upper end of the range
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
	3: Intermittent, low production.	3: High production, heavy use
	4: Large hood or large air mass in motion	4: Small hood-local control only
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.	
Individual protection measures, such as personal protective equipment		
Eye and face protection	► Safety glasses with side shields. ► Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent] ► Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.	
Skin protection	See Hand protection below	
Hands/feet protection	► No special equipment needed when handling small quantities. ► OTHERWISE: ► For potentially moderate exposures: ► Wear general protective gloves, eg. light weight rubber gloves. ► For potentially heavy exposures: ► Wear chemical protective gloves, eg. PVC. and safety footwear.	
Body protection	See Other protection below	
Other protection	No special equipment needed when handling small quantities. OTHERWISE: ► Overalls. ► Skin cleansing cream. ► Eyewash unit. ► Do not spray on hot surfaces.	

Respiratory protection

- Generally not applicable.

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Continued...

LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)

Appearance	Colourless		
Physical state	Compressed Gas	Relative density (Water = 1)	1.3-1.4
Odour	Characteristic	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	<1
Initial boiling point and boiling range (°C)	47.78	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	18	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	6.7	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	543.13	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	>1	VOC %	96.5%
Heat of Combustion (kJ/g)	7.09	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▶ Elevated temperatures. ▶ Presence of open flame. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	There is sufficient evidence to classify this material as acutely toxic.
b) Skin Irritation/Corrosion	There is sufficient evidence to classify this material as skin corrosive or irritating.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	There is sufficient evidence to classify this material as toxic to specific organs through single exposure
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.
Ingestion	Not normally a hazard due to physical form of product.
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Spray mist may produce discomfort
Eye	This material causes serious eye irritation.
Chronic	Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Main route of exposure to the gas in the workplace is by inhalation.

LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)

LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)	TOXICITY	IRRITATION
	Not Available	Not Available
TRANS-DICHLOROETHYLENE(R)	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >5000 mg/kg ^[1]	Eye (Rodent - rabbit): 10mg - Moderate
	Inhalation (Rat) LC50: 24100 ppm4h ^[1]	Eye: adverse effect observed (irritating) ^[1]
	Oral (Rat) LD50: 1235 mg/kg ^[2]	Skin (Rodent - rabbit): 500mg/24H - Moderate
		Skin: no adverse effect observed (not irritating) ^[1]
1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Not Available
	Inhalation (Rat) LC50: >24.619 mg/L4h ^[1]	
	Oral (Rat) LD50: >2000 mg/kg ^[1]	
carbon dioxide	TOXICITY	IRRITATION
	Not Available	Not Available

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Acute Toxicity	✓	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity					
LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
TRANS-DICHLOROETHYLENE(R)	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	220mg/l	2
	EC50(ECx)	48h	Algae or other aquatic plants	36.36mg/l	4
	LC50	96h	Fish	135mg/l	2
1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>213mg/l	2
	EC50	48h	Crustacea	>94mg/l	2
	NOEC(ECx)	96h	Fish	<73mg/l	2
	LC50	96h	Fish	>76mg/l	2
carbon dioxide	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	35mg/l	1
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.
Wastes resulting from use of the product must be disposed of on site or at approved waste sites.
DO NOT discharge into sewer or waterways.

Persistence and degradability

LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)

Ingredient	Persistence: Water/Soil	Persistence: Air
TRANS-DICHLOROETHYLENE(R)	HIGH	HIGH
1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*	HIGH	HIGH
carbon dioxide	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
TRANS-DICHLOROETHYLENE(R)	LOW (LogKOW = 2.09)
1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*	LOW (LogKOW = 2.2978)
carbon dioxide	LOW (LogKOW = 0.83)

Mobility in soil

Ingredient	Mobility
TRANS-DICHLOROETHYLENE(R)	LOW (Log KOC = 43.79)
1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*	LOW (Log KOC = 125.3)
carbon dioxide	HIGH (Log KOC = 1.498)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Where in doubt contact the responsible authority.
------------------------------	--

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	NO

Land transport (TDG)

14.1. UN number or ID number	1950		
14.2. UN proper shipping name	AEROSOLS		
14.3. Transport hazard class(es)	Class	2.2	
	Subsidiary Hazard	Not Applicable	
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
14.6. Special precautions for user	Special provisions		80, 107
	Explosive Limit and Limited Quantity Index		1 L
	ERAP Index		Not Applicable

Air transport (ICAO-IATA / DGR)

14.1. UN number	1950		
14.2. UN proper shipping name	Aerosols, non-flammable		
14.3. Transport hazard class(es)	ICAO/IATA Class	2.2	
	ICAO / IATA Subsidiary Hazard	Not Applicable	
	ERG Code	2L	
14.4. Packing group	Not Applicable		
14.5. Environmental hazard	Not Applicable		
14.6. Special precautions for user	Special provisions	A98 A145 A167 A802	
	Cargo Only Packing Instructions	203	

LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)

Cargo Only Maximum Qty / Pack	150 kg
Passenger and Cargo Packing Instructions	203
Passenger and Cargo Maximum Qty / Pack	75 kg
Passenger and Cargo Limited Quantity Packing Instructions	Y203
Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1950	
14.2. UN proper shipping name	AEROSOLS	
14.3. Transport hazard class(es)	IMDG Class	2.2
	IMDG Subsidiary Hazard	Not Applicable
14.4. Packing group	Not Applicable	
14.5 Environmental hazard	Not Applicable	
14.6. Special precautions for user	EMS Number	F-D, S-U
	Special provisions	63 190 277 327 344 381 959
	Limited Quantities	1000 ml

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code
Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
TRANS-DICHLOROETHYLENE(R)	Not Applicable
1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*	Not Applicable
carbon dioxide	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
TRANS-DICHLOROETHYLENE(R)	Not Applicable
1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*	Not Applicable
carbon dioxide	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

TRANS-DICHLOROETHYLENE(R) is found on the following regulatory lists

- Canada Categorization decisions for all DSL substances
- Canada Domestic Substances List (DSL)
- Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether* is found on the following regulatory lists

- Canada Domestic Substances List (DSL)

carbon dioxide is found on the following regulatory lists

- Canada Categorization decisions for all DSL substances
- Canada Domestic Substances List (DSL)
- Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS
- FEI Equine Prohibited Substances List - Controlled Medication
- FEI Equine Prohibited Substances List (EPSL)

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIC / Australia Non-Industrial Use	No (1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*)
Canada - DSL	Yes
Canada - NDSL	No (TRANS-DICHLOROETHYLENE(R); 1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*; carbon dioxide)

LPS® Instant Super Degreaser 2.0 / MAX Instant Super Degreaser 2.0 (Aerosol)

National Inventory	Status
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*)
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	No (1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*)
Philippines - PICCS	No (1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*)
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	No (1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*)
UAE - Control List (Banned/Restricted Substances)	No (TRANS-DICHLOROETHYLENE(R); 1,1,2,2-tetrafluoroethyl-2,2,2-trifluoroethyl ether*; carbon dioxide)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	17/10/2025
Initial Date	20/09/2025

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Powered by AuthorITe, from Chemwatch.