LPS® Detex® Food Grade Silicone (Aerosol)

ITW Pro Brands. -GA

Part Number: **01716**
Version No: **1.1**
Safety Data Sheet according to OSHA HazCom Standard (2024) requirements

Initial Date: **15/11/2025**
Revision Date: **14/11/2025**
Print Date: **19/11/2025**
S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	LPS® Detex® Food Grade Silicone (Aerosol)
Proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	For Industrial Use Only Use according to manufacturer's directions.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	**ITW Pro Brands. -GA**
Address	4647 Hugh Howell Rd. Tucker, GA United States
Telephone	770-243-8800
Fax	Not Available
Website	www.itwprobrands.com
Email	lpssds@itwprobrands.com

Emergency phone number

Association / Organisation	**Dykem/Dymon/Scrubs = Call InfoTrac For_LPS & Other Brands = Call Chemtrec**
Emergency telephone number(s)	**1-800-535-5053 (InfoTrac Inside US) 1-800-424-9300 (Chemtrec Inside US)**
Other emergency telephone number(s)	**1-352-323-3500 (Infotrac Ouside US) +001 703-527-3887 (Chemtrec Outside US)**

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

Classification	Aerosols, Hazard Category 1, Skin Corrosion/Irritation Category 2, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Reproductive Toxicity Category 2

Label elements

Hazard pictogram(s)	
Signal word	**Danger**

Hazard statement(s)

H222+H229	Extremely flammable aerosol. Pressurized container: may burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Page 1 continued...

P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing gas.
P280	Wear protective gloves and protective clothing.
P202	Do not handle until all safety precautions have been read and understood.
P264	Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64742-49-0	60-80	Hydrocarbons, C6, isoalkanes, <5% n-hexane (US only)
68476-86-8.	10-30	LPG (liquefied petroleum gas) sweetened
110-54-3	<0.25	n-hexane***

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If aerosols come in contact with the eyes: ▸ Immediately hold the eyelids apart and flush the eye with fresh running water. ▸ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▸ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If solids or aerosol mists are deposited upon the skin: ▸ Flush skin and hair with running water (and soap if available).. ▸ Seek medical attention in the event of irritation.
Inhalation	If aerosols, fumes or combustion products are inhaled: ▸ Remove to fresh air. ▸ Lay patient down. Keep warm and rested. ▸ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▸ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▸ Transport to hospital, or doctor.
Ingestion	Not considered a normal route of entry. ▸ If spontaneous vomiting appears imminent or occurs, hold patients head down, lower than their hips to help avoid possible aspiration of vomitus.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

SMALL FIRE:

▸ Water spray, dry chemical or CO2

Continued...

LARGE FIRE:
- Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility	‣ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting	---------- GENERAL ---------- ‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ May be violently or explosively reactive. ‣ Wear breathing apparatus plus protective gloves. ‣ Consider evacuation ‣ Fight fire from a safe distance, with adequate cover. ‣ If safe, switch off electrical equipment until vapour fire hazard removed. ‣ Use water delivered as a fine spray to control fire and cool adjacent area. ‣ **DO NOT** approach cylinders suspected to be hot. ‣ Cool fire-exposed cylinders with water spray from a protected location. ‣ If safe to do so, remove containers from path of fire. ---------- FIRE FIGHTING PROCEDURES: ---------- ‣ The only safe way to extinguish a flammable gas fire is to stop the flow of gas. ‣ If the flow cannot be stopped, allow the entire contents of the cylinder to burn while cooling the cylinder and surroundings with water from a suitable distance. ‣ Extinguishing the fire without stopping the gas flow may permit the formation of ignitable or explosive mixtures with air. These mixtures may propagate to a source of ignition. ---------- SPECIAL HAZARDS ---------- ‣ Excessive pressures may develop in a gas cylinder exposed in a fire; this may result in explosion. ‣ Cylinders with pressure relief devices may release their contents as a result of fire and the released gas may constitute a further source of hazard for the fire-fighter. ‣ Cylinders without pressure-relief valves have no provision for controlled release and are therefore more likely to explode if exposed to fire. ---------- FIRE FIGHTING REQUIREMENTS: ---------- The need for proximity, entry and flash-over protection and special protective clothing should be determined for each incident, by a competent fire-fighting safety professional. Prevent by any means spillage from entering drains or water-courses.
Fire/Explosion Hazard	‣ Liquid and vapour are flammable. ‣ Moderate fire hazard when exposed to heat or flame. ‣ Vapour forms an explosive mixture with air. ‣ Moderate explosion hazard when exposed to heat or flame. ‣ Vapour may travel a considerable distance to source of ignition. ‣ Heating may cause expansion or decomposition leading to violent rupture of containers. ‣ Aerosol cans may explode on exposure to naked flame. ‣ Rupturing containers may rocket and scatter burning materials. ‣ Hazards may not be restricted to pressure effects. ‣ May emit acrid, poisonous or corrosive fumes. ‣ On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) other pyrolysis products typical of burning organic material.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	‣ Clean up all spills immediately. ‣ Avoid breathing vapours and contact with skin and eyes. ‣ Wear protective clothing, impervious gloves and safety glasses. ‣ Shut off all possible sources of ignition and increase ventilation. ‣ Wipe up. ‣ If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. ‣ Undamaged cans should be gathered and stowed safely.
Major Spills	‣ DO NOT exert excessive pressure on valve; DO NOTattempt to operate damaged valve. ‣ Clear area of personnel and move upwind. ‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ May be violently or explosively reactive. ‣ Wear breathing apparatus plus protective gloves. ‣ Prevent, by any means available, spillage from entering drains or water courses ‣ No smoking, naked lights or ignition sources. ‣ Increase ventilation. ‣ Stop leak if safe to do so. ‣ Water spray or fog may be used to disperse / absorb vapour. ‣ Absorb or cover spill with sand, earth, inert materials or vermiculite. ‣ If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. ‣ Undamaged cans should be gathered and stowed safely.

Continued...

	▸ Collect residues and seal in labelled drums for disposal.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▸ Avoid all personal contact, including inhalation. ▸ Wear protective clothing when risk of exposure occurs. ▸ Use in a well-ventilated area. ▸ Prevent concentration in hollows and sumps. ▸ **DO NOT** enter confined spaces until atmosphere has been checked. ▸ Avoid smoking, naked lights or ignition sources. ▸ Avoid contact with incompatible materials. ▸ When handling, **DO NOT** eat, drink or smoke. ▸ **DO NOT** incinerate or puncture aerosol cans. ▸ **DO NOT** spray directly on humans, exposed food or food utensils. ▸ Avoid physical damage to containers. ▸ Always wash hands with soap and water after handling. ▸ Work clothes should be laundered separately. ▸ Use good occupational work practice. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS. ▸ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. **NFPA 30B Storage Level: 3**
Other information	▸ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can ▸ Store in original containers in approved flammable liquid storage area. ▸ **DO NOT** store in pits, depressions, basements or areas where vapours may be trapped. ▸ No smoking, naked lights, heat or ignition sources. ▸ Keep containers securely sealed. Contents under pressure. ▸ Store away from incompatible materials. ▸ Store in a cool, dry, well ventilated area. ▸ Avoid storage at temperatures higher than 40 deg C. ▸ Store in an upright position. ▸ Protect containers against physical damage. ▸ Check regularly for spills and leaks. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS. ▸ Do not cut, drill, grind, weld or perform similar operations on or near containers. Containers, even those that have been emptied, can contain explosive vapours.

Conditions for safe storage, including any incompatibilities

Suitable container	▸ Aerosol dispenser. ▸ Check that containers are clearly labelled.
Storage incompatibility	▸ Avoid reaction with oxidising agents



+	x	+	x	+	+	+

X — *Must not be stored together*
0 — *May be stored together with specific preventions*
\+ — *May be stored together*

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	n-hexane***	n-Hexane	500 ppm / 1800 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	n-hexane***	n-Hexane	50 ppm / 180 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
Hydrocarbons, C6, isoalkanes, <5% n-hexane (US only)	1,000 mg/m3	11,000 mg/m3	66,000 mg/m3
n-hexane***	260 ppm	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
Hydrocarbons, C6, isoalkanes, <5% n-hexane (US only)	Not Available	Not Available
n-hexane***	Not Available	Not Available
LPG (liquefied petroleum gas) sweetened	Not Available	Not Available

Continued...

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
The basic types of engineering controls are:
Process controls which involve changing the way a job activity or process is done to reduce the risk.
Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection.
Provide adequate ventilation in warehouse or closed storage areas.
Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Speed:
aerosols, (released at low velocity into zone of active generation)	0.5-1 m/s
direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment



Eye and face protection

- Safety glasses with side shields.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.

Skin protection

See Hand protection below

Hands/feet protection

- Wear general protective gloves, eg. light weight rubber gloves.

Body protection

See Other protection below

Other protection

No special equipment needed when handling small quantities.
OTHERWISE:

- Overalls.
- Skin cleansing cream.
- Eyewash unit.
- Do not spray on hot surfaces.

Respiratory protection

Type KAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Colourless

Physical state	Liquified Gas	**Relative density (Water = 1)**	0.66
Odour	Characteristic, Slight	**Partition coefficient n-octanol / water**	>1
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Available
pH (as supplied)	Not Applicable	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (cSt)**	<20.5
Initial boiling point and boiling range (°C)	61	**Molecular weight (g/mol)**	Not Available
Flash point (°C)	<17	**Taste**	Not Available
Evaporation rate	<1	**Explosive properties**	Not Available
Flammability	HIGHLY FLAMMABLE.	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	6	**Surface Tension (dyn/cm or mN/m)**	Not Available

Continued...

Lower Explosive Limit (%)	1	**Volatile Component (%vol)**	96
Vapour pressure (kPa)	46.93	**Gas group**	Not Available
Solubility in water	Immiscible	**pH as a solution (1%)**	Not Available
Vapour density (Air = 1)	Not Available	**VOC %**	96.03%
Heat of Combustion (kJ/g)	>30	**Ignition Distance (cm)**	Not Available
Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available
Nanoform Solubility	Not Available	**Nanoform Particle Characteristics**	Not Available
Particle Size	Not Available		

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▸ Elevated temperatures. ▸ Presence of open flame. ▸ Product is considered stable. ▸ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	There is sufficient evidence to classify this material as skin corrosive or irritating.
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	There is sufficient evidence to classify this material as toxic to reproductivity
h) STOT - Single Exposure	There is sufficient evidence to classify this material as toxic to specific organs through single exposure
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. **WARNING**:Intentional misuse by concentrating/inhaling contents may be lethal.
Ingestion	Considered an unlikely route of entry in commercial/industrial environments
Skin Contact	This material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility. Main route of exposure to the gas in the workplace is by inhalation.

LPS® Detex® Food Grade Silicone (Aerosol)

TOXICITY	IRRITATION
Not Available	Not Available

Hydrocarbons, C6, isoalkanes, <5% n-hexane (US only)

TOXICITY	IRRITATION
dermal (rat) LD50: 3.35 mg/kg[2]	Eye: no adverse effect observed (not irritating)[1]
Inhalation (Rat) LC50: 0.26 mg/L4h[2]	Skin: adverse effect observed (irritating)[1]
Oral (Rat) LD50: 16.75 mg/kg[2]	

n-hexane*

TOXICITY	IRRITATION
Inhalation (Human) TCLo: 190 ppm/8W[2]	Eye (Rodent - rabbit): 10mg - Mild
Inhalation (Rat)LD50: 48000 ppm/4h[2]	Eye: no adverse effect observed (not irritating)[1]
Oral (Rat) LD50: 28710 mg/kg[2]	Skin: no adverse effect observed (not irritating)[1]

Continued...

LPG (liquefied petroleum gas) sweetened	

TOXICITY	IRRITATION
Inhalation (Rat) LC50: 658 mg/l4h[2]	Not Available

Legend:	***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***

Acute Toxicity	✗	**Carcinogenicity**	✗
Skin Irritation/Corrosion	✓	**Reproductivity**	✓
Serious Eye Damage/Irritation	✗	**STOT - Single Exposure**	✓
Respiratory or Skin sensitisation	✗	**STOT - Repeated Exposure**	✗
Mutagenicity	✗	**Aspiration Hazard**	✗

Legend: ✗ ***– Data either not available or does not fill the criteria for classification***
✓ ***– Data available to make classification***

SECTION 12 Ecological information

Toxicity

LPS® Detex® Food Grade Silicone (Aerosol)

Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

Hydrocarbons, C6, isoalkanes, <5% n-hexane (US only)

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	48h	Crustacea	0.64mg/l	2
EC50	96h	Algae or other aquatic plants	64mg/l	2
NOEC(ECx)	504h	Crustacea	0.17mg/l	2
LC50	96h	Fish	0.11mg/l	2

n-hexane***

Endpoint	Test Duration (hr)	Species	Value	Source
EC50(ECx)	4h	Algae or other aquatic plants	0.12mg/L	4
LC50	96h	Fish	113mg/L	4

LPG (liquefied petroleum gas) sweetened

Endpoint	Test Duration (hr)	Species	Value	Source
EC50	96h	Algae or other aquatic plants	7.71mg/l	2
EC50(ECx)	96h	Algae or other aquatic plants	7.71mg/l	2
LC50	96h	Fish	24.11mg/l	2

Legend: ***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data***

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
n-hexane***	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
n-hexane***	MEDIUM (LogKOW = 3.9)
LPG (liquefied petroleum gas) sweetened	LOW (LogKOW = 3.39)

Mobility in soil

Ingredient	Mobility
n-hexane***	LOW (Log KOC = 149)

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

Waste treatment methods

Continued...

Product / Packaging disposal	▸ Consult State Land Waste Management Authority for disposal. ▸ Discharge contents of damaged aerosol cans at an approved site. ▸ **DO NOT** incinerate or puncture aerosol cans. ▸ Bury residues and emptied aerosol cans at an approved site.

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	NO

Shipping container, transport vehicle placarding, and labeling may vary from the below information. This depends on the quantity shipped, the applicability of excepted quantity requirements, limited quantity requirements, and/or special provisions according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

Land transport (DOT)

14.1. **UN number or ID number**	1950
14.2. **UN proper shipping name**	Aerosols, flammable, (each not exceeding 1 L capacity)
14.3. **Transport hazard class(es)**	Class: 2.1 Subsidiary Hazard: Not Applicable
14.4. **Packing group**	Not Applicable
14.5. **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	Hazard Label: 2.1 Special provisions: N82

Air transport (ICAO-IATA / DGR)

14.1. **UN number**	1950
14.2. **UN proper shipping name**	Aerosols, flammable
14.3. **Transport hazard class(es)**	ICAO/IATA Class: 2.1 ICAO / IATA Subsidiary Hazard: Not Applicable ERG Code: 10L
14.4. **Packing group**	Not Applicable
14.5. **Environmental hazard**	Not Applicable
14.6. **Special precautions for user**	Special provisions: A145 A167 A802 Cargo Only Packing Instructions: 203 Cargo Only Maximum Qty / Pack: 150 kg Passenger and Cargo Packing Instructions: 203 Passenger and Cargo Maximum Qty / Pack: 75 kg Passenger and Cargo Limited Quantity Packing Instructions: Y203 Passenger and Cargo Limited Maximum Qty / Pack: 30 kg G

Sea transport (IMDG-Code / GGVSee)

14.1. **UN number**	1950
14.2. **UN proper shipping name**	AEROSOLS
14.3. **Transport hazard class(es)**	IMDG Class: 2.1 IMDG Subsidiary Hazard: Not Applicable
14.4. **Packing group**	Not Applicable
14.5 **Environmental hazard**	Marine Pollutant
14.6. **Special precautions for user**	EMS Number: F-D, S-U Special provisions: 63 190 277 327 344 381 959 Limited Quantities: 1000 ml

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Continued...

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Hydrocarbons, C6, isoalkanes, <5% n-hexane (US only)	Not Applicable
n-hexane***	Not Applicable
LPG (liquefied petroleum gas) sweetened	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
Hydrocarbons, C6, isoalkanes, <5% n-hexane (US only)	Not Applicable
n-hexane***	Not Applicable
LPG (liquefied petroleum gas) sweetened	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

Hydrocarbons, C6, isoalkanes, <5% n-hexane (US only) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic
US DOE Temporary Emergency Exposure Limits (TEELs)
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

n-hexane* is found on the following regulatory lists**

Chemical Footprint Project - Chemicals of High Concern List
US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants
US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity
US - California Proposition 65 - Reproductive Toxicity
US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List
US - Massachusetts - Right To Know Listed Chemicals
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Flammables
US - New Jersey Right to Know Hazardous Substances
US - Pennsylvania - Hazardous Substance List
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US Clean Air Act - Hazardous Air Pollutants
US DOE Temporary Emergency Exposure Limits (TEELs)
US EPA Integrated Risk Information System (IRIS)
US EPCRA Section 313 Chemical List
US New York City Community Right-to-Know: List of Hazardous Substances
US NIOSH Recommended Exposure Limits (RELs)
US OSHA Permissible Exposure Limits (PELs) Table Z-1
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

LPG (liquefied petroleum gas) sweetened is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Additional Regulatory Information

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	Yes
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No

Continued...

Acute toxicity (any route of exposure)	No
Reproductive toxicity	Yes
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
n-hexane***	5000	2270

US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372)

This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know-Act of 1986 (40 CFR 372):

CAS No	%[weight]	Name
110-54-3	<0.25	n-hexane***

This information must be included in all SDSs that are copied and distributed for this material.

Additional Federal Regulatory Information

Not Applicable

State Regulations

US. California Proposition 65

WARNING: This product can expose you to chemicals including **diethanolamine,** which is known to the State of California to cause cancer, and **n-hexane** which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (Hydrocarbons, C6, isoalkanes, <5% n-hexane (US only); n-hexane***; LPG (liquefied petroleum gas) sweetened)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (Hydrocarbons, C6, isoalkanes, <5% n-hexane (US only); LPG (liquefied petroleum gas) sweetened)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	No (Hydrocarbons, C6, isoalkanes, <5% n-hexane (US only); n-hexane***; LPG (liquefied petroleum gas) sweetened)
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 Other information

Revision Date	14/11/2025
Initial Date	15/11/2025

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Powered by AuthorITe, from Chemwatch.

Continued...

end of SDS