

Accu-Lube® #10 Perfect Tap Hand Applied Lubricants

FEATURES

- Natural based cutting oil
- Thick consistency
- For ferrous and non ferrous metals, aluminum and titanium

APPLICATIONS

- Tapping
- Reaming
- Drilling

DIRECTIONS

Its thickness allows to tap to cut several holes before recoating is necessary. Use sparingly, a little goes a long way.

HANDLING

Avoid contact with skin, eyes, clothing. Wash thoroughly after handling.

STORAGE

Keep container tightly closed in a dry and well-ventilated place.

DISPOSAL INFORMATION

Dispose of contents/container to an approved waste disposal plant.



PHYSICAL PROPERTIES

Appearance/physical state	Liquid
Odor	Mild
Melting point/freezing point	No data available
Boiling point/range	>400°F/ >204°C
Vapor pressure	<1 mmHg
Partition coefficient	No data available
Percent volatile	No data available
Flammability limit	No data available
Propellant	N/A
VOC Content	Negligible
Color	Pink
Flash point	>200°F/ >93°C
Relative density	No data available
Evaporation rate	No data available
Vapor density	>1
Auto-ignition temperature	No data available
Viscosity	No data available
Specific Gravity (water=1)	0.92
Temperature Range °F(°C)	No data available
4-Ball Weld Load	No data available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
----------	--------------	----------------	------------	-------------



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved