

# Rustlick™ 606 Rust Preventative

## DESCRIPTION

Rustlick™ 606 is a moisture-absorbing rust preventative and corrosion inhibitor designed for long-term in-door use which can be applied to porous, wet surfaces and reduces surface preparation time. It leaves an oily thin-film that is easily removed by wiping, alkaline washing, or vapor degreasing. Rustlick™ 606 is recommended for porous or configured metals.

## FEATURES

- Indoor corrosion protection for up to two years
- Spreads into nooks, crannies, pores and gaps
- Leaves a transparent rust-inhibiting film

## APPLICATIONS

- For corrosion and rust prevention

## DIRECTIONS

Aerosol: Spray on wherever protection is needed, Bulk: Apply by brushing or dipping

## HANDLING

Aerosol: Keep away from heat, sparks and open flame. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Bulk: Keep away from heat, sparks and open flame. No smoking. Use only in area provided with appropriate exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Wear personal protective equipment. Wash thoroughly after handling.

## STORAGE

Aerosol: Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. Bulk: Keep away from open flames, hot surfaces and sources of ignition. Keep container tightly closed in a dry and well-ventilated place.

## DISPOSAL INFORMATION

Dispose of contents/container to an approved waste disposal plant.



## PROPERTIES

<b>Appearance/physical state</b>	Aerosol: Aerosol, Bulk: Liquid
<b>Odor</b>	Aerosol: Mild, Bulk: Characteristic
<b>Melting point/freezing point</b>	Not Available
<b>Boiling point/range</b>	Aerosol: No data available, Bulk: 100 °C / 212 °F
<b>Vapor pressure</b>	No data available
<b>Partition coefficient</b>	No data available
<b>Percent volatile</b>	No data available
<b>Flammability limit</b>	No data available
<b>Propellant</b>	Aerosol:
<b>VOC Content</b>	72%
<b>Color</b>	Red Brown
<b>Flash point</b>	Aerosol: -104 °C / -156 °F , Bulk: 79 °C / 175 °F
<b>Relative density</b>	Not Available
<b>Evaporation rate</b>	>1
<b>Vapor density</b>	>1
<b>Auto-ignition temperature</b>	No data available
<b>Viscosity</b>	No data available
<b>Specific Gravity (water=1)</b>	Aerosol: 0.86, Bulk: 0.83
<b>Temperature Range °F(°C)</b>	Not Available
<b>4-Ball Weld Load</b>	Not Available

## SHELF LIFE INFORMATION

2 years



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved



# 606 Rust Preventative

---

## AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
71102	12 wt oz	aerosol	12	13 lbs
71052	5 gal	pail	1	36 lbs
71152	1 gal	case	4	30 lbs
71552	55 gal	drum	1	411 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved