



# A-151 Solvent Degreaser



## FEATURES

- Controlled evaporation
- Ideal for parts washers, dip tanks, and ultrasonic cleaners
- Contains no chlorinated solvents
- Removes oil, grease and other contaminants
- Non-conductive, low odor
- VOC compliant in all 50 states
- High flash point 158°F (70°C)

## APPLICATIONS

- Aircraft engine components
- Bearings
- Cables
- Chains
- Dip tanks
- Electric Motors
- Gauges
- Gears
- Heavy Equipment
- High-voltage cable connections
- Parts washers
- Ultrasonic Cleaner

## SPECIFICATIONS AND APPROVALS

- Airbus ABR 9-0140 Type I
- ASTM F-945
- Boeing D6-17487 Rev. P
- Embraer EMB 120 Brasilia C.P.M.-120/1181 Type B-1
- Honda Corp.
- Kimberly-Clark
- Learjet LES1239J
- McDonnell Douglas CSD #1
- NSF® International - Aerosol
- NSF® International - Non-Aerosol
- Xerox

## PROPERTIES

<b>Appearance/physical state</b>	Gas/Aerosol
<b>Odor</b>	Mild
<b>Melting point/freezing point</b>	Not available
<b>Boiling point/range</b>	383°F (195°C)
<b>Vapor pressure</b>	< 0.1 mm Hg @ 20°C
<b>Partition coefficient</b>	Not available
<b>Percent volatile</b>	100%
<b>Flammability limit</b>	Not available
<b>Propellant</b>	Carbon dioxide
<b>VOC Content</b>	0 % per U.S. State and Federal Consumer Product Regulations
<b>Color</b>	Clear water-white
<b>Flash point</b>	158.0°F (70.0°C) Tag Closed Cup
<b>Evaporation rate</b>	< 0.1 BuAc
<b>Vapor density</b>	6.1 (air = 1)
<b>Auto-ignition temperature</b>	> 381.2°F (> 194°C)
<b>Viscosity</b>	< 3 mm /s @ 25°C
<b>Relative Density</b>	Not available
<b>Temperature Range °F(°C)</b>	Not applicable
<b>4-Ball Weld Load</b>	Not applicable

## DIRECTIONS

Aerosol - Spray on parts and equipment. Bulk - Use in dip or spray applications. Allow flushing action to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying.

## HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. (see Section 7 of the SDS)

## STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Keep away from heat and sources of ignition. (see Section 7 of the SDS)

## DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Aerosol - Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

## AVAILABLE PRODUCTS

US	Part No.		Net Contents	Container Type	Units/Case	Case Weight
	Canada	Europe				
		M04305	20 L	pail	1	
04320	C04320	M04320	15 wt oz / 425 g / 498 mL	aerosol	12	15 lbs
04305	C04305		5 gal / 18.93 L	pail	1	40 lbs
04355	C04355		55 gal / 208 L	drum	1	375 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved