

FEATURES

- Foam clings to vertical surfaces minimizing wasteful run-off
- Contains no chlorine, hydrochlorine, sulfuric, phosphoric or other harmful mineral acids
- Removes dirt, soap scum, stains caused by mildew, mold or algae
- Also removes oxidation, corrosion, urine, salts, light rust, lime, calcium and iron deposits
- Do not contain chlorine nor hydrochloric, sulfuric, phosphoric, or other harmful mineral acids

APPLICATIONS

- Grout
- Rubber

Imitation MarbleAnodized Metals

• Fittings & Equipment

- Plastic
- Brass
- Copper

- Stainless Steel
- Ceramic Tile
- Painted MetalsChrome Fixtures
- Fiberglass

DIRECTIONS

Lightly spray foam on surface, allow to sit 5-10 seconds, permitting product to attack contaminants. Wipe surface, and rinse well. Repeat if necessary.

HANDLING

Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands, and any exposed skin thoroughly after handling. Wear protective gloves, protective clothing, eye protection, face protection.

STORAGE

Store locked up.

DISPOSAL

Dispose of contents/container to an approved waste disposal plant.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
33732	32 fl oz / 946.4 mL	bottle	12 bottles 1 trigger sprayer	29 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved



PROPERTIES Appearance / Phys

FROFERILES			
Appearance / Physical State	Liquid		
Odor	Pine		
Melting / Freezing Point	N/A		
Boiling Point / Range	100°C / 212°F		
Vapor Pressure	N/A		
Partition Coefficient	N/A		
Flammability	Not flammable (N/A)		
VOC Content	1.00%		
Color	Yellow		
Evaporation Rate	N/A		
Vapor density	> 1 (air = 1)		
Viscosity	2.5 cps		
Specific Gravity	1.011 @ 70°F		
pH Value	1.3		