



# AT-30

## Corrosion Inhibitor

### FEATURES

- Light protective film
- Easy to clean
- Washes clean with warm water
- Will not varnish after multiple applications

### APPLICATIONS

- Spray, brush, roll coat or drip application on cold and hot rolled steel.

### DIRECTIONS

Dilute Metal Mates AT-30 with water to suit the specific application. Normal Protection: 3% NOTE: These dilution ratios should only be used as general guidelines and are not exact specifications.

### HANDLING

Use appropriate safety equipment. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from extreme heat. Keep container closed when not in use.

### STORAGE

Store away from extreme heat, flame, or ignition sources. Pressure buildup may occur due to heat exposure or temperature change. Release pressure by slowly opening container.

### DISPOSAL

Absorb on suitable material and follow procedures listed below. Dispose of in a manner that is recommended by local, state, provincial and federal laws and regulations.



### PROPERTIES

Appearance / Physical State	liquid
Odor	amine odor
pH Value	8.0-9.0 at 10%
Specific Gravity	1.04
Boiling Point / Range	212F (100C)
Vapor Pressure	<1 mmHg
Vapor Density	>1
Prop 65 Warning	No
Refractometer Readings	3-8 RI
Dilution Ratio	3:1 to 10:1

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Color
MM4203	55 gal	drum	1	clear, light amber
MM4206	330 gal	tote	1	clear, light amber



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved