



AT-30

Corrosion Inhibitor

Metal Mates AT-30 is an in-process / short-term rust preventive that is typically applied at 3% dilution. This water-based product dries to a light, non-tacky film and provides excellent corrosion protection for steel parts.

FEATURES

- Light protective film
- Easy to clean

APPLICATIONS

- Spray, brush, roll coat or drip application on cold and hot rolled steel.

DIRECTIONS

Dilute Metal Mates AT-30 with water to suit the specific application. Normal Protection: 3% NOTE: These dilution ratios should only be used as general guidelines and are not exact specifications.

HANDLING

Use appropriate safety equipment. Use with adequate ventilation. Avoid contact with eyes, skin and clothing. Keep away from extreme heat. Keep container closed when not in use.

STORAGE

Store away from extreme heat, flame, or ignition sources. Pressure buildup may occur due to heat exposure or temperature change. Release pressure by slowly opening container.

DISPOSAL

Absorb on suitable material and follow procedures listed below. Dispose of in a manner that is recommended by local, state, provincial and federal laws and regulations.



PROPERTIES

Appearance / Physical State	liquid
Odor	amine odor
pH Value	8.0-9.0 at 10%
Specific Gravity	1.04
Boiling Point / Range	212F (100C)
Vapor Pressure	<1 mmHg
Vapor Density	>1
Prop 65 Warning	No
Refractometer Readings	3-8 RI
Dilution Ratio	3:1 to 10:1

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Color
MM4203	55 gal	drum	1	clear, light amber
MM4206	330 gal	tote	1	clear, light amber



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved