

Accu-Lube® Accu-Lube Universal Brass MQL Applicator

FEATURES

- Exclusive air-driven positive displacement pump technology delivers precise metered amount of lubricant
- Can be either manually controlled by the operator, or integrated into machinery controls
- Air filter/regulator gives added control and precision
- Lockable security box with front and back door access
- Individually controlled airflow valve(s), lubricant control, and frequency generator(s) allow for customization of up to 16 pumps in various configurations (4 line groups, 8 line groups, asymmetrical groupings, etc.)
- No misting! Coaxial hose assembly atomizes the lubricant at the nozzle tip prevents misting
- Fixed and moveable nozzles available
- Can be permanently mounted, or magnetically attached & moved as needed

APPLICATIONS

- Delivery of precise amounts of lubricant to any externally-lubricated application, such as: Milling, Drilling, Sawing (band & circular), Turning, Tapping, etc.
- Brass pumps either manually or solenoid-controlled

DIRECTIONS

See Accu-Lube Applicator User Manual for installation and use instructions.

HANDLING

Use normal handling procedures consistent with medium-sized/weight packages prior to installation. Once installed guard from accidental bumps or collisions that may damage the applicator, lines, or nozzles.

STORAGE

To avoid damaged or lost parts, keep in a dry and well-ventilated place in the original packaging until ready to install.

AVAILABLE PRODUCTS

Part No.	Container Type
01B0	1 Brass Nozzle, Manual
02B0	2 Brass Nozzle, Manual
01B1	1 Brass Nozzle, 110 VAC
02B1	2 Brass Nozzle, 110 VAC
01B3	1 Brass Nozzle, 24 VDC
02B3	2 Brass Nozzle, 24 VDC



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved