

FEATURES

- Designed to remove grease and soil
- Clinging foam permits long lasting contact with surfaces to be cleaned
- Use to clean countertops, walls, cabinets, and greasy parts

APPLICATIONS

Plastic

Metal

• Ceramic

- Urethane
- Concrete
- and more

DIRECTIONS

Spray evenly over surface. Wipe clean or spray with clean water. For heavily soiled surfaces, have product remain on surface for an extended period of time.

HANDLING

Shake well before using. Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

STORAGE

Protect from sunlight. Store in a well-ventilated place. May explode if heated. KEEP OUT OF REACH OF CHILDREN.

DISPOSAL INFORMATION

Dispose of contents/container according to local/national disposal regulations.



PROPERTIES

Appearance/physical state	te Aerosol		
Odor	Citrus		
Vapor pressure	60 psig @ 21°C (70°F)		
Flammability limit	Not applicable		
Propellant	Isobutane/propane blend		
VOC Content	7.99%		
Color	Colorless		
Flash point	N/A		
Relative density	Not determined		
Evaporation rate	N/A		
Vapor density	> 1 (Air=1)		
Auto-ignition temperature	Product is not self-igniting		
Viscosity	Not determined		
Density @ 20°C (68°F)	1.01 g/cm (8.428 lbs/gal)		
pH Value	9.8 - 11.0		
Solubility in Water	Soluble		

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
19220	18 oz. (510 g)	aerosol	12	18 lbs.

