



FEATURES

- Water-based formula that prevents weld spatter from ticking to metal
- Biodegradable with non-toxic, non-flammable formula
- Contains no silicone
- Paint compatible
- Eliminates the need for chiseling, grinding, or brushing after welding
- Oversized E-Z Spray Nozzle; ideal when wearing welding gloves

APPLICATIONS

- Tampa Electric Co.

PROPERTIES

Appearance/physical state	Liquid/Gas
Odor	Not Significant
Melting point/freezing point	N/A
Boiling point/range	212°F (100°C)
Vapor pressure	N/A
Partition coefficient	<1
Percent volatile	95%-97%
Flammability limit	N/A
Propellant	Nitrogen
VOC Content	0%
Color	Opaque, Milky
Flash point	None
Relative density	0.99 - 1.01 @ 20°C (water = 1)
Evaporation rate	1 (water = 1)
Vapor density	N/A
Auto-ignition temperature	N/A
Viscosity	N/A
Specific Gravity (water=1)	0.99 - 1.01 (water = 1)

DIRECTIONS

Shake well and apply/spray onto clean surface if possible. Spray and light even coat.

HANDLING

Wash hands after handling.

STORAGE

Contains gas under pressure; may explode if heated. Store in a well-ventilated place.

DISPOSAL INFORMATION

Dispose of waste and residues in accordance with local authority requirements.