



BFX

All-Purpose Cleaner



FEATURES

- Removes dirt and grime from hard surfaces
- Safe to use on most surfaces except for magnesium
- Water-based for safer cleaning alternative
- Non-corrosive formula to inhibit flash rusting
- Does not contain butyl or phosphates
- Ideal for pressure washers
- Conforms to VOC regulations in US and Canada
- Contoured can for improved hand grip

APPLICATIONS

- Aluminum
- Chrome
- Counters
- Floors
- Machinery
- Painted Surfaces
- Soft metals
- Spot Cleaning
- Vents
- Walls

SPECIFICATIONS AND APPROVALS

- NSF International, C1

PROPERTIES

Appearance / Physical State	Liquid
Color	Colorless to light yellow
Odor	Sassafras
pH Value	11.8
Boiling Point / Range	212°F (100°C)
Flash Point	None
Evaporation Rate	1 BuAc
Vapor Pressure	17.5 mm Hg @ 20°C
Vapor density	>1
Water Solubility	100%
Viscosity	1 cSt @ 20°C
Density	8.5 lb/gal (estimated)
Percent volatile	99%
Specific Gravity	1.02
VOC Content	0% per US State & Federal Consumer Product Regulations

DIRECTIONS

(Trigger) Turn nozzle to spray or stream position. Pull trigger to spray.
 (Bulk) KEEP FROM FREEZING. MIX WELL BEFORE USING. Rinse and/or wipe dry any residue. Test for compatibility on delicate materials.
 Dilution Ratio Product:
 Water Equipment Applications
 1: 4 Parts Washers Carbon blocks, engines, exhaust hoods, forklifts, graffiti, marine, tanks, varnish
 1: 5 Dip Tanks Aviation, compressors, food processing equipment, floors, hoists, lifts, printing presses, tools
 1: 7 Tumblers Drill presses, oily parts, pulleys and wires
 1: 10 Ultrasonic Cleaning electrical parts (Deionized water rinse/dry)
 1: 4-20 Steam Cleaner Engines, parts
 1: 60 Trigger Sprayer Floors, leather and fabrics, tile, walls, wood
 1: 40-80 Pressure Washer Cleaning parts, floors, trucks, etc.
 1: 100 Trigger Sprayer Appliances, formica, general cleaning of glass, walls

HANDLING

Avoid prolonged exposure. Observe good industrial hygiene practices.

STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
05528	C05528	28 fl oz / 828 mL	trigger	12	27 lbs
05501		1 gal / 3.78 L	bottle	4	37 lbs
05555	C05555	55 gal / 208 L	drum	1	535 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved