



# BRITE-MARK® Jumbo

Permanent Paint Marker/Valve Action

## DIRECTIONS FOR USE

- Shake well with cap on
- Depress tip to start flow
- Replace cap when not in use

## FEATURES

- BRITE-MARK® is a general purpose paint marker that writes on almost any surface.
- BRITE-MARK® is available in 5 marker styles - BRITE-MARK® Medium, BRITE-MARK® Roughneck®, BRITE-MARK® PM 40 , BRITE-MARK® Fine and BRITE-MARK® Jumbo
- Makes permanent bright marks on metal, rubber, plastic, glass, concrete, leather, stone, wood, vinyl and more.
- Quick drying, oil based, UV resistant paint withstands harsh indoor and outdoor conditions.
- "Does not contain any HAP's (Hazardous Air Pollutants) which makes them a smart alternative to using spray paint and stencil for big, bold marks. "
- Does not contain any reportable amounts of Xylene.
- Markers can be used to permanently identify inventory, assemblies, tools, finished products or work in progress while resisting most work related abuses or compounds.
- Valve action mechanism prevents paint in barrel from drying when the cap is left off.
- Bullet tips are replaceable to assure complete use of paint in each marker.
- BRITE-MARK® Medium, Roughneck®, PM 40, and Jumbo have a heavy duty aluminum body with large paint capacity.
- BRITE-MARK® Medium is our top selling marker with a felt tip for smooth, even marks.
- BRITE-MARK® 40 features a threaded cap and barrel that can be screwed into a jig or fixture for a continuous marking process.
- BRITE-MARK® Roughneck® has a tough polyester tip designed to write through grease, dirt, water and oil.
- BRITE-MARK® Fine is a light weight marker that writes fine, distinctive marks.
- BRITE-MARK® Jumbo is designed to write broad marks, over 0.5 inch wide, visible from long distances.

## MATERIALS COMPATIBILITY

- Safe on most surfaces.
- Removable with DYKEM® Remover & Cleaner.
- Surface tests should be run to determine compatibility prior to use.

## HEALTH AND SAFETY

- Flammable liquid and vapor. Keep away from heat, sparks and flame. Use only with adequate ventilation. Avoid contact with skin and eyes.
- Refer to SDS (Safety Data Sheet) for complete information on health and safety. Visit our website at [www.dykem.com](http://www.dykem.com) to obtain an MSDS.



## PHYSICAL PROPERTIES

Appearance	Varies
Odor	Sweet
VOC level	45% - 77% by weight
Flash point	81°F
Shelf Life**	24 Months
Dry Time*	25-30 seconds
* Note: Drying time may vary depending on film	

## AVAILABLE IN

Part #
Colors
Black*
Blue*
Green*
Red*
Orange*
White*
Yellow*
Gold
Silver
Violet
Pink
Brown
Lt Blue
* Tested and confi



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved