



Belt Dressing



FEATURES

- NSF H1 lubricant can be used anywhere within a facility where incidental food contact may occur
- Prevents belt slippage and squeaks on all belt types
- Withstands frequent washdowns, extending maintenance cycles and reducing downtime
- Contains no chlorinated solvents that deteriorate drive belts
- May be used indoors or in wet/outdoor conditions
- Metal and X-ray detectable packaging

APPLICATIONS

- Appliance Drive Belts
- Bearings
- Bushings
- Flat Belts
- Polishing Belts
- Round Belts

SPECIFICATIONS AND APPROVALS

- Canadian Food Inspection Agency
- Ford Motor Co.
- General Motors Co.
- Kimberly-Clark
- NSF International, H1
- Whirlpool

PROPERTIES

Appearance / Physical State	Gas
Color	Clear. Colorless.
Odor	Hydrocarbon-like.
Melting / Freezing Point	Not available.
Boiling Point / Range	195.8°F (91°C) (concentrate)
Flash Point	19.4°F (-7.0°C) Tag Closed Cup
Evaporation Rate	> 1 BuAc
Flammability	lower: 0.6%; upper: 7%
Vapor Pressure	Not available.
Partition Coefficient	Not available.
Vapor Density	Not available.
Auto-Ignition Temperature	Not available.
Viscosity	Not available.
Density	5.74 lb/gal
Percent volatile	90%
Specific Gravity	0.67 - 0.69 @ 20°C
VOC Content	90%
Propellant	Propane/Butane
Temperature Range	32°F (0°C) to 325°F (163°C)

DIRECTIONS

Shake well before using. Turn off equipment and stop belts before applying. Spray inner surface of belt from a distance of 6 to 8 inches. Use only enough to cover belt. Let vapors dissipate. If desired, attach extension tube for difficult to reach areas. Repeat as needed. Avoid contamination of food in the application and storage of the product. Do not add directly to food. Use only in well ventilated areas. Avoid all sources of ignition (spark or flame).

HANDLING

Turn can upside-down and spray to clear nozzle. Wear protective gloves/eye protection/face protection. Wash hands thoroughly after handling.

STORAGE

Keep container closed and in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F. Store aerosols as Level 3 Aerosol (NFPA 30B). Product is stable under recommended storage conditions. Keep away from heat and ignition sources. Do not expose to direct sunlight for extended periods.

DISPOSAL

Waste must be disposed of in accordance with national, regional, provincial, and local environmental control regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
02216	C02216	10 wt oz / 284 g / 433 mL	aerosol	12	11 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved