

Accu-Lube® Block Lube

Hand Applied Lubricant

FEATURES

- Hand held solid lubricant
- Reduces heat build up in belt, disc and wheel grinding application
- Vegetable-based
- For ferrous & nonferrous metals, aluminum and titanium
- Clean with soap and water

APPLICATIONS

- Belt, disc and wheel grinding

DIRECTIONS

Apply directly to the tool or work area for immediate lubrication

HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling

STORAGE

Keep container tightly closed in a dry and well-ventilated place.

DISPOSAL INFORMATION

Dispose of in accordance with local regulations.



PHYSICAL PROPERTIES

Appearance/physical state	Solid
Odor	Mild
Melting point/freezing point	110-120°F/43-49°C
Boiling point/range	>400°F/>204°C
Vapor pressure	< 1 mmHg
Partition coefficient	No data available
Percent volatile	No data available
Flammability limit	No data available
Propellant	N/A
VOC Content	None
Color	Blue
Flash point	>200°F/>93°C
Relative density	No data available
Evaporation rate	No data available
Vapor density	>1
Auto-ignition temperature	No data available
Viscosity	No data available
Specific Gravity (water=1)	0.86
Temperature Range °F(°C)	No data available
4-Ball Weld Load	No data available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
79037	2.6 wt oz	bar	120	25 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved