



Carbide Powergrind Synthetic Grinding Fluid

DESCRIPTION

Carbide Powergrind is a premium synthetic metalworking fluid designed for carbide grinding. It prevents carbide damage and minimizes cobalt leaching. Transparent solution provides excellent lubricity and keeps wheels clean while providing dry-film corrosion protection for work pieces and machines.

FEATURES

- Recommended for machining tungsten carbide
- Contains inhibitors to prevent cobalt leaching from all grades of carbide
- Highly biostable and resistant to bacteria and fungus growth

APPLICATIONS

- Diamond wheel grinding

MATERIALS COMPATIBILITY

- Ferrous Metals
- Brass, Bronze, and Copper.
- Limited use on Stainless Steel.
- Limited use on Titanium.
- Not recommended for Cast Iron.
- Not recommended for Aluminum.

DIRECTIONS

PRODUCT/APPLICATOR TROUBLESHOOTING: Use a refractometer to measure coolant concentration
Use Triadine 20 or Grotan for microbial control in sump tanks
Call Technical Sales for detailed questions pertaining to the products



PROPERTIES

Appearance / Physical State	Opaque Green
Specific Gravity	1.04
Vapor Density	> 1
pH Value	10.2
Flash Point	>200°F
Boiling Point / Range	212°F
Active sulfur content	None
Total chlorine	None
Density	8.7 lbs/gal
Dilution Ratio	10:1 to 30:1
Water Solubility	Soluble in water

SHELF LIFE INFORMATION

1 year

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
74052	5 gal	pail	1	47 lbs
74552	55 gal	drum	1	506 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved