



ChainMate

Chain & Wire Rope Moly Lubricant



FEATURES

- Fortified with molybdenum disulfide
- Increases chain and wire rope life
- Effective under extreme pressure and temperature ranges
- Contains water displacing solvents to quickly penetrate into cracks and core of wire rope
- Anti-sling adhesion
- Reduces wear caused by friction and corrosion
- Provides maximum lubrication and corrosion protection
- VOC compliant in all 50 state

APPLICATIONS

- Bushings
- Cables
- Chains
- Cranes
- Cutting tools
- Drag lines
- Drives
- Forklifts
- Pins
- Pulleys
- Rollers
- Saws
- Sprockets
- Wire ropes

SPECIFICATIONS AND APPROVALS

- Ford Motor Co.
- Pratt & Whitney Canada MMC 21530

PROPERTIES

Appearance / Physical State	Aerosol: Gas
Color	Dark grey. Black
Odor	Slight petroleum odor.
Flash Point	< -4.0°F (< -20.0°C) Tag Closed Cup
Flammability	Flammable gas.
Vapor Pressure	35 psi @ 75°F
Vapor density	> 1
Water Solubility	16%
Viscosity	150 cP @ 75°F / 23.9°C
Density	7.32
Heat of Combustion	> 30 kJ/g
Percent Volatile	17% @ 110°F (43.33°C)
Specific Gravity	0.88 @ 20°C
VOC Content	22.33% per US State and Federal Consumer Product Regulations
Propellant	Petroleum Gases

DIRECTIONS

For best results, clean chain or wire rope before applying. Shake well before using, until ball moves freely. Hold can upright and spray from 10-12 inches away. Use attached extension tube for pinpoint application. Apply a light coating. Reapply as needed.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

STORAGE

Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store between 40°F (5°C) and 120°F (49°C). Store aerosols as Level 3 Aerosol (NFPA 30B). Store all materials in a dry, well ventilated area. Avoid breathing vapors

DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/ or regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
02416	C02416	11 wt oz / 312 g / 405 mL	aerosol	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved