



Cross Check™ Fast

Fast-Dry Torque Seal® Indicator Paste

HANDLING

- Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

DIRECTIONS

- Knead tube before use.
- Dries to the touch in less than a minute. Full cure time: 24 hours.

STORAGE

- Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

- Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations

FEATURES

- Tamper Proof Torque Mark
- Safe for most surfaces
- Highly visible
- Excellent adhesion
- Visually detects loose nuts & bolts
- Provides warranty protection
- Marks fluoresce under black/UV light.
- Patent 10,934,452



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid.
Odor	mild
Flash Point	23.0 °F (-5.0 °C) Tag Closed Cup
Boiling Point / Range	175 °F (79.44 °C)
VOC Content	42.28%, 430 g/L
Vapor Density	> 1
Prop 65 Warning	YES

AVAILABLE IN

Container Type	Units/Case	Color	Part #
1 oz	24	orange	83514



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved