



Cross Check™ Plus

Aviation Grade Torque Seal® - Skydrol® Resistant

HANDLING

- Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharge

STORAGE

- Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated

DISPOSAL INFORMATION

- Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable

FEATURES

- Dries to the touch: less than a minute
- Full cure time: 24 Hours
- Visually detect loose nuts and bolts
- Use on all critical fittings and locknuts during OEM and maintenance procedures
- Perfect for use on landing gear, rotor assemblies, gearboxes, Pal Nuts and more
- Excellent for marking quality procedures
- For use in any aircraft environment with possible fluid exposure
- 2-Year shelf life
- Patent-pending
- Provides warranty protection against tampering



PHYSICAL PROPERTIES

Physical State	Liquid
Odor	mild
Flash Point	23.0 °F (-5.0 °C) Tag Closed Cup
Boiling Point	175 °F (79.44 °C)
VOC Content	38 % w/w
Evaporation Rate	> 1
Vapor Density	> 1
Prop 65 Warning	YES
Disposal Information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable

AVAILABLE IN

Container Type	Units/Case	Color	Part #
1 oz.	24	Yellow	83417
1 oz.	24	Blue	83418
1 oz.	24	Pink	83420



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved