

Cross Check™ Plus

Aviation Grade Torque Seal® - Skydrol® Resistant

HANDLING

 Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protectmaterial from direct sunlight. When using do not smoke. Explosion-proof general and local exhaustventilation. Take precautionary measures against static discha

STORAGE

 Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic chargebuild-up by using common bonding and grounding techniques. Store in a cool, dry place out ofdirect sunlight. Store in tightly closed container. Store in a well-ventil

DISPOSAL INFORMATION

 Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate thematerial under controlled conditions in an approved incinerator. Do not incinerate sealedcontainers. If discarded, this product is considered a RCRA ignitab

FEATURES

- Dries to the touch: less than a minute
- Full cure time: 24 Hours
- Visually detect loose nuts and bolts
- Use on all critical fittings and locknuts during OEM and maintenance procedures
- Perfect for use on landing gear, rotor assemblies, gearboxes, Pal Nuts and more
- Excellent for marking quality procedures
- For use in any aircraft environment with possible fluid exposure
- 2-Year shelf life
- Patent-pending
- Provides warranty protection against tampering
- Meets Boeing Specification BMS8-45H, Type I/III







PHYSICAL PROPERTIES

Physical State	Liquid	
Odor	mild	
Flash Point	23.0 °F (-5.0 °C) Tag Closed Cup	
Boiling Point	175 °F (79.44 °C)	
VOC Content	38 % w/w	
Evaporation Rate	>1	
Vapor Density	>1	
Prop 65 Warning	YES	
Disposal Information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate thematerial under controlled conditions in an approved incinerator. Do not incinerate sealedcontainers. If discarded, this product is considered a RCRA ignitab	

AVAILABLE IN

Container Type	Units/Case	Color	Part #
1 oz.	24	Yellow	83417
1 oz.	24	Blue	83418
1 oz.	24	Pink	83420

