



# D'Gel

## Cable Gel Solvent



### FEATURES

- Safe on cable insulation and components, metals, and most plastics
- Preferred by Telecom workers
- Removes petroleum, polyethylene, and silicone based gels
- Rinses off with water and contains no chlorinated solvents
- Removes cable gels, blocking compounds, flooding and filling compounds, grease, tar, and oil
- Flash point above 140°F (60°C)
- Bellcore tested for complete compatibility with telco components

### APPLICATIONS

- Blocking Compounds
- Equipment
- Filling Compounds
- Forming Compounds
- Copper Cables
- Equipment
- Fiber Optic Cables
- Flooding Compounds
- Grease
- Removing Cable Gels
- Resin
- Tar
- Tools
- Wax
- Painted Surfaces
- Oil

### SPECIFICATIONS AND APPROVALS

- NASA MSFC-SPEC-2490, Rev B

### PROPERTIES

<b>Appearance / Physical State</b>	Liquid
<b>Odor</b>	Orange (Citrus)
<b>Melting / Freezing Point</b>	N/A
<b>Boiling Point / Range</b>	379.4°F (193°C) @ 760mmHg
<b>Vapor Pressure</b>	N/A
<b>Partition Coefficient</b>	<1
<b>Percent volatile</b>	97%
<b>Flammability</b>	Lower: 1.3%; Upper: 8.9%
<b>Color</b>	Colorless
<b>Flash Point</b>	161.60°F (72.00°C) (TCC)
<b>Density</b>	N/A
<b>Evaporation Rate</b>	< 10 (BuAc = 100)
<b>Vapor density</b>	> 1 (air = 1)
<b>Auto-Ignition Temperature</b>	N/A
<b>Viscosity</b>	< 3 cSt @ 25°C
<b>Specific Gravity</b>	0.78 - 0.8 @ 20°C

### DIRECTIONS

Apply to the cable using a saturated cloth, towel, or brush. Wipe towards the conductor. Allow the D'Gel solvent to evaporate (air dry) or wipe dry with a lint-free cloth. Soaking the cable may be desirable in some situations.

### HANDLING

Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

### STORAGE

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

### DISPOSAL

Dispose of content/container in accordance with local/regional/national/international regulations.

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
61201	1 gal / 3.78 L	can	4	32 lbs
61232	32 fl oz / 946 mL	bottle	12	22 lbs
61244	1 wipe	packet	144	6 lbs
61255	55 gal / 208 L	drum	1	380 lbs
61296	3 qts / 946 mL	pail	4	23 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved