



# EFX<sup>®</sup>

## Solvent Degreaser



### FEATURES

- Ideal for degreasing metals; safe on most plastics
- Fast-acting solvent minimizes downtime
- Fast evaporating, leaves no residue
- Power blast spray instantly removes oil, grease, wax, dirt, tar and other contaminants
- Contains no chlorinated solvents
- Contoured can for improved hand grip

### APPLICATIONS

- Air Compressors
- Air Tools
- Bearings
- Bonding prep
- Chains
- Cranes
- Engines
- Forklifts
- Gears
- Machinery
- Pulleys
- Wire Cables

### AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
01855		55 gal / 208 L	drum	1	
01820	C01820	15 wt oz / 425 g / 588 mL	aerosol	12	15 lbs

### PROPERTIES

<b>Appearance / Physical State</b>	Aerosol: Gas, Bulk: Liquid
<b>Color</b>	Colorless
<b>Odor</b>	Characteristic
<b>Boiling Point / Range</b>	140.9°F (60.5°C)
<b>Flash Point</b>	21.2°F (-6.0°C) Tag Closed Cup -- dispensed liquid
<b>Evaporation Rate</b>	1.6 (water = 1)
<b>Flammability</b>	Lower: 1.5%, Upper: 9%
<b>Vapor Density</b>	2.8 (estimated)
<b>Water Solubility</b>	<10%
<b>Partition Coefficient</b>	>1
<b>Auto-Ignition Temperature</b>	582.8°F (306°C)
<b>Viscosity</b>	< 3 cSt @ 25°C
<b>Percent volatile</b>	100%
<b>Specific Gravity</b>	0.65 - 0.68 @ 20°C
<b>VOC Content</b>	Aerosol: 86.9 %, Bulk: 90%

### DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

### HANDLING

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. (see Section 7 of the SDS)

### STORAGE

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. (see Section 7 of the SDS)

### DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS<sup>®</sup>, SCRUBS<sup>®</sup>, DYKEM<sup>®</sup>, Accu-Lube<sup>®</sup>, DYMON<sup>®</sup>, Spray Nine<sup>®</sup>, and Cedar<sup>®</sup> are registered trademarks and Rustlick<sup>™</sup>, Diamondkote<sup>™</sup>, and MetalMates<sup>™</sup> are trademarks of Illinois Tool Works • All Rights Reserved