



# EVR™

## Clean Air Solvent Degreaser



### FEATURES

- High solvent strength, ideal for cleaning metals
- Fast Evaporating
- Leaves extremely low residue
- Inverta Spray Valve can be sprayed at any angle
- Contains no ozone depleting compounds
- Excellent alternative to Methyl Ethyl Ketone (MEK)
- Conforms to VOC regulations in US and Canada
- Instant cleaning action
- Complies with SCAQMD (South Coast Air Quality Management District) Rule 102
- Contoured can for improved hand grip

### APPLICATIONS

- Bearings
- Brakes
- Controls
- Cables
- Chains
- Gauges
- Gears
- Heavy Equipment
- De-energized Cable Connectors
- Instruments
- Machinery
- Metal Prep
- Pulleys
- Welding Equipment

### SPECIFICATIONS AND APPROVALS

- NSF International, C1 (Aerosol)

### PROPERTIES

<b>Appearance / Physical State</b>	Aerosol: Gas, Bulk: Liquid
<b>Color</b>	Clear. Colorless.
<b>Odor</b>	Slight. Orange.
<b>Melting / Freezing Point</b>	Not established
<b>Boiling Point / Range</b>	132.8°F (56°C)
<b>Flash Point</b>	-0.4°F (-18.0°C) Tag Closed Cup
<b>Evaporation Rate</b>	5.6 - 6.1
<b>Flammability</b>	Lower (%) 2.5%; Upper (%) 12.8%
<b>Vapor Pressure</b>	Aerosol: 3452mm Hg@20°C; Bulk: 185 mm Hg @20°C
<b>Auto-Ignition Temperature</b>	869°F (465°C)
<b>Viscosity</b>	14 cSt @ 25°C
<b>Density</b>	6.59
<b>Percent volatile</b>	100%
<b>Specific Gravity</b>	0.79 @ 20°C
<b>VOC Content</b>	0.5% per US State and Federal Consumer Product Regulations
<b>Propellant</b>	Carbon dioxide

### DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

### HANDLING

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. (see Section 7 of the SDS)

### STORAGE

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. (see Section 7 of the SDS)

### DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
05220	14 wt oz / 397 g/ 492 mL	aerosol	12	15 lbs
05205	5 gal / 18.93 L	pail	1	40 lbs
05255	55 gal / 208 L	drum	1	369 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMOM®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved