



FEATURES

- Quick Penetration
- Does not contain HCFCs or other chlorinated solvents
- Ideal for electronic and fine partsRemoves light greases, oils, dirt, and organic soils
- Non-Conductive
- Meets CARB and OTC regulations

APPLICATIONS

- Connectors
- Contacts
- Controls
- Office Equipment
- Telecommunication EquipmentPrinted Circuits
- Switches

Sensors

PROPERTIES

Appearance/physical state	Liquid/Gas		
Odor	Strong		
Melting point/freezing point	N/A		
Boiling point/range	158°F (70°C)		
Vapor pressure	>100 mm Hg @20°C		
Partition coefficient	>1		
Percent volatile	100%		
Flammability limit	Lower: 4%; Upper: 8%		
Propellant	HFC-134a		
VOC Content	70.1%		
Color	Colorless		
Flash point	<73.4°F (< 23.0°C) (TCC)		
Relative density	N/A		
Evaporation rate	6 BuAc		
Vapor density	~4.3 (air = 1)		
Auto-ignition temperature	>914 °F (> 490°C)		
Viscosity	N/A		
Specific Gravity (water=1)	1.29 - 1.32 @20°C		

DIRECTIONS

Hold can 6-8 inches away and spray directly on surface to clean. Check on inconspicuous area before using.

HANDLING

Do not handle until all safety precautions have been reas and understood. Do not breathe gas. Washer thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.

STORAGE

Store in a well-ventilated place. Keep container tighly closed. Store locked up. Protect from sunlight.

DISPOSAL INFORMATION

Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.					
US	Canada	Net Contents	Container Type	Units/Case	Case Weight
00816	C00816	12 wt oz / 340 g / 268 mL	aerosol	12	13 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved