



Electra-X

Contact Cleaner



FEATURES

- Quick Penetration
- Does not contain HCFCs or other chlorinated solvents
- Ideal for electronic and fine parts
- Removes light greases, oils, dirt, and organic soils
- Non-Conductive
- Meets CARB and OTC regulations

APPLICATIONS

- Connectors
- Contacts
- Controls
- Office Equipment
- Sensors
- Telecommunication Equipment
- Printed Circuits
- Switches

PROPERTIES

Appearance / Physical State	Liquid/Gas
Odor	Strong
Melting / Freezing Point	N/A
Boiling Point / Range	158°F (70°C)
Vapor Pressure	>100 mm Hg @20°C
Partition Coefficient	>1
Percent volatile	100%
Flammability	Lower: 4%; Upper: 8%
Propellant	HFC-134a
VOC Content	70.1%
Color	Colorless
Flash Point	<73.4°F (< 23.0°C) (TCC)
Density	N/A
Evaporation Rate	6 BuAc
Vapor density	~4.3 (air = 1)
Auto-Ignition Temperature	>914 °F (> 490°C)
Viscosity	N/A
Specific Gravity	1.29 - 1.32 @20°C

DIRECTIONS

Hold can 6-8 inches away and spray directly on surface to clean. Check on inconspicuous area before using.

HANDLING

Do not handle until all safety precautions have been read and understood. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.

STORAGE

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.

DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
00816	12 wt oz / 340 g / 268 mL	aerosol	12	13 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved