



# Electro 140° Contact Cleaner



## FEATURES

- Non-flammable and non-conductive
- Safe on plastics
- Ideal for electrical/electronic fine parts
- Removes light greases, oils, dirt, and organic soils
- Fast Evaporating, no residue
- Quick Penetrating
- Conforms to VOC regulations in US and Canada
- Contoured can for improved hand grip

## APPLICATIONS

- Calculators
- Communication Equipment
- Computers
- Digital Equipment
- Electrical Contacts
- Electrical Equipment
- Electronic Ignitions
- HVAC Systems
- Navigation Equipment
- Printed Circuit Boards
- Servers
- Switches & Relays
- Radars & Radios
- Robotic Equipment

## SPECIFICATIONS AND APPROVALS

- Ford Motor Co.

## PROPERTIES

Appearance / Physical State	Gas
Color	Clear, colorless.
Odor	Characteristic.
Melting / Freezing Point	N/A
Boiling Point / Range	383°F (195°C)
Flash Point	158°F (70°C) Tag Closed Cup
Evaporation Rate	< 0.1 BuAc
Flammability	Lower: 0.6%, Upper: 20.4% (estimated)
Vapor Pressure	<0.1 mm Hg @ 20°C
Vapor Density	6.1 (air = 1)
Water Solubility	Not soluble in water.
Partition Coefficient	>1
Auto-Ignition Temperature	>381.2°F (>194°C)
Viscosity	< 3 mm <sup>2</sup> /s
Heat of Combustion	> 30 kJ/g
Specific Gravity	0.84 - 0.86 @ 20°C (water=1)
VOC Content	0% per U.S. State and Federal Consumer Product Regulations
Propellant	Carbon Dioxide

## DIRECTIONS

Hold can 6-8 inches (15-20 cm) away from electronic components and spray directly on surface to clean. May attack certain plastics.

## HANDLING

Pressurized container: do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection/face protection.

## STORAGE

Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Keep away from heat, hot surface sparks, open flames, and other ignition sources.

## DISPOSAL

Dispose of waste and residues in accordance with local authority requirements.

## AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
00916	C00916	11 wt oz / 312 g / 389 mL	aerosol	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved