



Food Grade Electronic Cleaner

w/DETEX[®]



FEATURES

- Removes dirt, moisture, oxides, from electronic equipment
- Plastic safe and ideal for cleaning delicate precision mechanisms
- Rapidly evaporates and leaves no residue
- Manufactured for the food industry and safe to use in all plant areas
- VOC Compliant in all 50 states

APPLICATIONS

- Breakers
- Connectors
- Contacts
- Controls
- Digital Equipment
- Office Equipment
- Printed Circuits
- Switches

SPECIFICATIONS AND APPROVALS

- NSF International, K6

PROPERTIES

Appearance / Physical State	Gas.
Color	Clear. Colorless.
Odor	Hydrocarbon-like.
Melting / Freezing Point	Not available.
Boiling Point / Range	136.99 °F (58.33 °C) Dispensed liquid.
Flash Point	< 1.4 °F (< -17.0 °C) (TCC)
Evaporation Rate	< 1 BuAc (Ethyl Ether = 1)
Flammability	Not available.
Vapor Pressure	352.53 mm Hg @ 38°C
Vapor density	> 1 (air = 1)
Water Solubility	<10%
Partition Coefficient	Not available.
Auto-Ignition Temperature	Not available.
Viscosity	< 3 cSt
Density	5.65
Percent volatile	100%
Specific Gravity	0.68
VOC Content	74%
Propellant	HFC-152a

DIRECTIONS

Hold can 15-20 cm (6-8 inches) away and spray directly onto electronic device or circuit board to eliminate and remove contaminants such as dirt, dust, moisture, flux or oxides.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not reuse empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

STORAGE

Level 2 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Protect from freezing.

DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
58116	C58116	11 oz	aerosol	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved