



FoodLube® Bearing Grease



FEATURES

- Uses only FDA listed ingredients
- Ensures safety in areas where incidental food contact may occur
- High degree of water washout resistance
- Excellent corrosion protection
- Very good load capacity
- Does not contain solvents or silicone
- Non-staining and non-emulsifying
- Metal Detectable Plastic Cap

APPLICATIONS

- Blending Machines
- Carton Erectors
- Feed Belts
- Filling Equipment
- Frequent Wash Down Area
- Labeling Stations
- Wrapping Equipment

SPECIFICATIONS AND APPROVALS

- Canadian Food Processors
- Meets FDA Regulation 21 CFR 178.3570
- NSF International, H1

PROPERTIES

Appearance / Physical State	Solid. Paste.
Color	White
Odor	Hydrocarbon-like.
Melting / Freezing Point	Not established.
Boiling Point / Range	Not available.
Flash Point	400.0 °F (204.4 °C) Tag Closed Cup
Evaporation Rate	< 1 (BuAc = 1)
Vapor Pressure	Not established.
Vapor density	< 1 (air = 1)
Specific Gravity	0.87 @ 15°C
Water Solubility	Not soluble.
Partition Coefficient	>1
Auto-Ignition Temperature	Not available
NLGI Grade	2
Thickener Type	Aluminum Complex
Base Oil Type	USP Grade White Mineral Oil
Viscosity	112 cst @ 40°C
Dropping Point	>450°F (>232.2°C)
Temperature Range	0°F (-18°C) to 300°F (149°C)
4-Ball Weld Load	>250 kg
Timken OK Load	40 lb
Water Washout	<1%
Copper Corrosion	Not available.

DIRECTIONS

For use in areas where incidental food contact may occur or in applications where clean, non-toxic lubricants are preferred. Apply either manually or by a suitable applicator. For best results, bearings should be purged of their previous lubricant before introducing new grease.

HANDLING

Observe good industrial hygiene practices.

STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
70114	C70114	14.1 oz / 400 g	cartridges	30	32 lbs
70155		55 gal / 400 lbs	drum	1	450 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved