



# G-49™

## Orange Degreaser Low VOCs



### FEATURES

- Excellent high solvent strength degreaser removes grease, grime, oil, ink, and adhesives
- Controlled evaporation increases dwell time to reduce effort in removing contaminants
- Conforms to VOC regulations in US and Canada
- Excellent alternative to Methyl Ethyl Ketone (MEK)
- Not a Hazardous Air Pollutant (HAP)
- No ozone depleting compounds (ODC)
- Inverta SprayValve can be sprayed at almost any angle
- Contoured can for improved hand grip

### APPLICATIONS

- Bearings
- Cables
- Chains
- De-energized Cable Connections
- Forklifts
- Gauges
- Gears
- Heavy Equipment
- Instruments
- Machinery
- Motors
- Pulleys
- Tools
- Welding Equipment

### SPECIFICATIONS AND APPROVALS

- NSF International, C1

### PROPERTIES

Appearance / Physical State	Gas/Aerosol
Color	Clear water-white
Odor	Acetone/Orange
Flash Point	-4.0 °F (-20.0 °C) Tag Closed Cup (estimated)
Evaporation Rate	0.2 BuAc
Flammability	Flammability limit: Lower = 2.5%, Upper = 12.8%
Density	6.7 lb/gal @ 25°C
Percent volatile	100%
Specific Gravity	0.81 @ 20°C
VOC Content	9.45%
Propellant	Carbon dioxide

### DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

### HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)

### STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat and sources of ignition. (See Section 7 of the SDS)

### DISPOSAL

Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
06420	15 wt oz / 425 g / 528 mL	aerosol	12	15 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved