



GREZ-OFF

Parts Cleaner Degreaser

FEATURES

- Professional Strength
- Water-Based
- Biodegradable

APPLICATIONS

- Engines
- Machinery
- Tools
- Movers
- Conveyors
- Vents
- Work Benches
- Walls and Floors
- Ovens
- Grills
- Trunks
- Trailers
- RV's
- Industrial and Farm Equipment
- Concrete
- Rubber

DIRECTIONS

1. Before degreasing, be sure that all surfaces are cool to the touch. Do not apply in direct sunlight or if air temperature is above 100°F. 2. Spray Grez-Off® full strength onto the cool, pretested surface to be degreased. 3. Allow Grez-Off® to penetrate soil. NEVER allow Grez-Off® to dry on any surface. Stubborn soils may require brushing or a second application. 4. Immediately rinse with water until no sudsing is noticeable.

HANDLING

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

STORAGE

Keep container tightly closed in a dry and well-ventilated place. Keep from freezing.

DISPOSAL INFORMATION

Disposal should be in accordance with applicable regional, national and local laws and regulations.



PROPERTIES

Appearance/physical state	Liquid
Odor	Citrus
Melting point/freezing point	No information available
Boiling point/range	100°C / 212°F
Vapor pressure	18 mm Hg
Partition coefficient	No information available
Percent volatile	No information available
Flammability limit	No information available
Propellant	N/A
VOC Content	
Color	Orange
Flash point	<1%
Relative density	-1.013 g/ml
Evaporation rate	<1
Vapor density	>1
Auto-ignition temperature	No information available
Viscosity	No information available
Specific Gravity (water=1)	No information available
Temperature Range °F(°C)	No information available
4-Ball Weld Load	No information available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
22701	1 gal.	Flat	4	36 lbs.
22705	5 gal.	Pail	1	46 lbs.
22732	32 oz.	Flat	12	29 lbs.
22755	55 gal.	Drum	1	504 lbs.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved