

GREZ-OFF®

Parts Cleaner Degreaser

FEATURES

- · Profesional Strength
- Water-Based
- Biodegradable

APPLICATIONS

- Engines
- Machinery
- Tools
- Movers
- Conveyors
- Vents
- Work Benches
- Walls and Floors
- Ovens
- Grills
- Trunks
- Trailers
- RV's
- Industrial and Farm Equipment
- Concrete
- Rubber



1. Before degreasing, be sure that all surfaces are cool to the touch. Do not apply in direct sunlight or if air temperature is above 100°F. 2. Spray Grez-Off® full strength onto the cool, pretested surface to be degreased. 3. Allow Grez-Off® to penetrate soil. NEVER allow Grez-Off® to dry on any surface. Stubborn soils may require brushing or a second application. 4. Immediately rinse with water until no sudsing is noticeable.

HANDLING

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

STORAGE

Keep container tightly closed in a dry and well-ventilated place. Keep from freezing.

DISPOSAL

Disposal should be in accordance with applicable regional, national and local laws and regulations.



PROPERTIES

Appearance / Physical State	Liquid		
Color	Orange		
Odor	Citrus		
pH Value	11.9 - 12.9		
Melting / Freezing Point	Not available.		
Boiling Point / Range	100°C / 212°F		
Flash Point	> 93 °C / > 199 °F		
Evaporation Rate	<1		
Vapor Pressure	18 mm Hg		
Vapor density	>1		
Water Solubility	Soluble.		
VOC Content	<1%		
Specific Gravity	1.013		

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
22701	1 gal.	Flat	4	36 lbs.
22705	5 gal.	Pail	1	46 lbs.
22732	32 oz	Flat	12	29 lbs.
22755	55 gal.	Drum	1	504 lbs.

