

# Accu-Lube® Gel Paste

## Hand-Applied Lubricants

### FEATURES

- Vegetable-based gel lubricant
- Workable texture makes it easy to apply to small and large tools
- Horizontal applications
- For ferrous & nonferrous metals, aluminum and titanium

### APPLICATIONS

- Short-run machining
- Tapping
- Drilling
- Reaming

### DIRECTIONS

Apply sparingly, directly on the tool.

### HANDLING

None required under normal usage.

### STORAGE

Keep containers tightly closed in a dry, cool and well-ventilated place.

### DISPOSAL INFORMATION

Dispose of in accordance with local regulations.



### PHYSICAL PROPERTIES

Appearance/physical state	Liquid
Odor	Mild
Melting point/freezing point	No data available
Boiling point/range	>200°C
Vapor pressure	No data available
Partition coefficient	No data available
Percent volatile	No data available
Flammability limit	No data available
Propellant	N/A
VOC Content	10.07
Color	Blue
Flash point	>93°C
Relative density	No data available
Evaporation rate	No data available
Vapor density	No data available
Auto-ignition temperature	No data available
Viscosity	No data available
Specific Gravity (water=1)	0.84
Temperature Range °F(°C)	No data available
4-Ball Weld Load	No data available

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
79030	8 oz	bottle	16	10 lbs
79035	5 gal	pail	1	46 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved