

Accu-Lube® Gel Paste

Manually-Applied Lubricants

FEATURES

- Vegetable-based gel lubricant clings better to parts and tooling
- Workable texture makes it easy to apply to small and large tools
- Horizontal applications
- For ferrous & nonferrous metals, aluminum and titanium

APPLICATIONS

- Short-run machining
- Tapping
- Drilling
- Reaming

DIRECTIONS

Apply sparingly, directly on the tool.

HANDLING

Observe good industrial hygiene practices. Avoid contact with skin, eyes, clothing. Wash thoroughly after handling.

STORAGE

Keep containers tightly closed in a dry, cool and well-ventilated place.

DISPOSAL

Dispose of in accordance with local regulations.



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Odor	Mild
Boiling Point / Range	>200°C
VOC Content	10.07
Color	Blue
Flash Point	>93°C
Specific Gravity	0.84

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
79030	8 oz	bottle	16	10 lbs
79035	5 gal	pail	1	46 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved