



# Graffiti & Spray Paint Remover

## Paint & Ink Remover

### FEATURES

- Removes paint, lipstick, grease, ball point ink, and crayons from a variety of surfaces
- Safe for cleaning metal, procelain, formica, and baked enamel paints
- Jelled aerosol formula that will not drip or run off vertical surfaces
- Product stays on surface long enough to emulsify hard-to-remove paint and graffiti
- Available in wipe form on SCRUBS line

### APPLICATIONS

- Fiberglass
- Aluminum
- Enamels
- Ceramic Tile
- Porcelain
- Steel
- Chrome
- Marble
- Formica
- Glass
- Brick & Concrete
- Brass

### DIRECTIONS

Shake well before using. Spray onto marks, wait 5-10 minutes for contact time on surface, then remove with a cloth. Stubborn soils: repeat application, let stand for 30-60 minutes, then remove with cloth. Refer to product label for more in depth removal instructions for heavy build up.

### HANDLING

Wear suitable personal protection equipment as required. After skin contact, immediately wash with water and soap and rinse with water. If exposed or concerned, get immediate medical attention.

### STORAGE

Keep away from heat/sparks/open flames/hot surfaces. No Smoking. Do not pierce or burn, even after use. Store locked up. Protect from sunlight. Do not exposed to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

### DISPOSAL INFORMATION

Dispose of contents/container in accordance with local/regional/national/international regulations. KEEP OUT OF REACH OF CHILDREN.

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
07820	17.5 oz. (496 g)	aerosol	12	18 lbs.



### PROPERTIES

Appearance/physical state	Aerosol
Odor	Aromatic
Melting point/freezing point	Undetermined
Boiling point/range	N/A (as aerosol)
Vapor pressure	125 psig @21°C (70°F)
pH	6.3 - 7.3
Flammability limit	N/A
Propellant	Propane/Isobutane blend
VOC Content	49.60%
Color	Light Tan
Flash point	< 2°C (< 36°F) (liquid)
Relative density	Not Determined
Evaporation rate	N/A
Vapor density	> 1 (Air=1)
Auto-ignition temperature	Not Determined
Viscosity	Not Determined
Density @ 21°C (70°F)	0.94 g/cm (7.844 lbs/gal)



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved