



HDX

Heavy-Duty Degreaser



FEATURES

- Removes oil, grease, wax, dirt, moisture, tar and other contaminants
- Non-flammable
- Fast evaporating
- Quick penetration
- Non-conductive
- No rinsing
- No residue

APPLICATIONS

- Air Compressors
- Air Conditioning Compressors
- Appliances
- Bearings
- Cables
- Chains
- Clutches
- Coils
- Controlys
- Conveyors
- Engines
- Forklifts
- Gauges
- Gear Drives
- Gears
- Handtrucks
- Heavy Equipment
- Pneumatic Hand Tools
- Pulleys
- Springs
- Starters
- Welding Instruments

SPECIFICATIONS AND APPROVALS

- NSF International, K1 (Aerosol)
- NSF International, K1 (Non Aerosol)

PROPERTIES

Appearance / Physical State	Gas(Aerosol), Liquid(Bulk)
Odor	Sweet, Spice
Melting / Freezing Point	Not established
Boiling Point / Range	188.6°F (87°C)
Vapor Pressure	58 mm Hg @ 20°C
Partition Coefficient	2.4
Percent volatile	100%
Flammability	per/lower flammability or explosive limits Flammability limit - lower (%) 8% Flammability limit - upper (%) 10.5%
Propellant	Carbon Dioxide (aerosol)
VOC Content	97.4% (aerosol) 100% (bulk) per US State & Federal Consumer Product Regulations
Color	Clear, Colorless
Flash Point	None
Density	Not established
Evaporation Rate	0.3 (Ethyl Ether = 1)
Vapor density	4.5
Auto-Ignition Temperature	> 788°F (> 420°C)
Viscosity	0.53 cP @ 25°C
Specific Gravity	1.41 - 1.47 @ 20°C
Temperature Range	Not applicable
4-Ball Weld Load	Not applicable

DIRECTIONS

(Aerosol) Hold can 6-8 inches away and spray directly on surface to degrease. (Bulk) Apply to metal parts and equipment and allow HDX to run off. Remove excess with a soft wipe or let air dry. If equipment is still dirty or greasy, repeat procedure. Test rubber and plastic surfaces for compatibility. After degreasing is complete, protect the equipment with your choice of LPS lubricants and corrosion inhibitors.

HANDLING

Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.

STORAGE

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
01020	C01020	19 wt oz / 539 g / 376 mL	aerosol	12	18 lbs
01005	C01005	5 gal / 18.93 L	pail	1	65 lbs
01055		55 gal / 208 L	drum	1	720 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved