



# HDX

## Heavy-Duty Degreaser



### FEATURES

- Removes oil, grease, wax, dirt, moisture, tar and other contaminants
- Non-flammable
- Fast evaporating
- Quick penetration
- Non-conductive
- No rinsing
- No residue

### APPLICATIONS

- Air Compressors
- Air Conditioning Compressors
- Appliances
- Bearings
- Cables
- Chains
- Clutches
- Coils
- Controls
- Conveyors
- Engines
- Forklifts
- Gauges
- Gear Drives
- Gears
- Handtrucks
- Heavy Equipment
- Pneumatic Hand Tools
- Pulleys
- Springs
- Starters
- Welding Instruments

### SPECIFICATIONS AND APPROVALS

- NSF International, K1 (Aerosol)
- NSF International, K1 (Non Aerosol)

### PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Clear, Colorless
Odor	Sweet, Spice
Boiling Point / Range	188.6°F (87°C)
Flash Point	None
Evaporation Rate	0.3 (Ethyl Ether = 1)
Flammability	Flammability limit: Lower = 8%, Upper = 10.5%
Vapor Pressure	58 mm Hg @ 20°C
Vapor density	4.5
Water Solubility	0.1%
Partition Coefficient	2.4
Auto-Ignition Temperature	> 788°F (> 420°C)
Viscosity	0.53 cP @ 25°C
Percent volatile	100%
Specific Gravity	1.41 - 1.47 @ 20°C
Propellant	Carbon Dioxide (aerosol)
VOC Content	Aerosol: 97.8%, Bulk: 100%

### DIRECTIONS

(Aerosol) Hold can 6-8 inches away and spray directly on surface to degrease. (Bulk) Apply to metal parts and equipment and allow HDX to run off. Remove excess with a soft wipe or let air dry. If equipment is still dirty or greasy, repeat procedure. Test rubber and plastic surfaces for compatibility. After degreasing is complete, protect the equipment with your choice of LPS lubricants and corrosion inhibitors.

### HANDLING

Do not handle until all safety precautions have been read and understood. Do not apply to hot surfaces. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.

### STORAGE

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

### DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

### AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
01020	C01020	19 wt oz / 539 g / 376 mL	aerosol	12	18 lbs
01005	C01005	5 gal / 18.93 L	pail	1	65 lbs
01055		55 gal / 208 L	drum	1	720 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved