



# Hi-Temp Bearing Grease



## FEATURES

- Reduces the risk of bearing failure at high temperatures
- Resists carbonization at high temperatures
- Extends relubrication periods
- Excellent vibration resistance
- Very high dropping point
- Reduces grease consumption
- Reduces the need for multiple greases

## APPLICATIONS

- Aluminum Castings
- Boiler Room Equipment
- Crucibles
- Engine Room Equipment
- Processing Ovens
- Shrink Wrappers

## PROPERTIES

<b>Appearance / Physical State</b>	Solid/Semi-solid.
<b>Color</b>	Amber
<b>Odor</b>	Slight.
<b>Flash Point</b>	> 442.4 °F (> 228.0 °C)
<b>Thickener Type</b>	Lithium Complex
<b>Base Oil Type</b>	PAO/Mineral Oil
<b>Viscosity</b>	165-195 cSt @ 40°C
<b>NLGI Grade</b>	2
<b>Dropping Point</b>	525°F (274°C)
<b>Temperature Range</b>	-5°F (-20°C) to 440°F (227°C)
<b>4-Ball Weld Load</b>	400 kg
<b>Copper Corrosion</b>	1B
<b>Timken OK Load</b>	60 lb

## DIRECTIONS

For use in environments that require exceptionally high temperature resistance. Apply either manually or by a suitable applicator. For best results, bearings should be purged of their previous lubricant before introducing new grease.

## HANDLING

Observe good industrial hygiene practices.

## STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

## AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
70214	C70214	14.1 oz / 400 g	cartridge	30	32 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved