High Purity
Markers

HANDLING

- Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

STORAGE

- Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL INFORMATION

- Dispose of contents/container in accordance with local/regional/national/international regulations.

FEATURES

- Permanent, valve-action mechanism prevents paint in barrel from drying when cap is left off
- Drying time: 45 seconds - 1 minute

PHYSICAL PROPERTIES

Physical State	Liquid.
Odor	various
Flash Point	89.0 - 108.0 °F (31.7 - 42.2 °C)
Boiling Point	248 - 338 °F (120 - 170 °C)
VOC Content	71.9%, 669 g/L
Evaporation Rate	< 1 (BuAc = 1)
Vapor Density	> 1 (air = 1)
Prop 65 Warning	YES

AVAILABLE IN

Units/Case	Marker Tip	Color	Part #
12	threaded cap tip	yellow	44916
12	threaded cap tip	white	44729
12	threaded cap tip	blue	44534
12	threaded cap tip	black	44404
12	threaded cap tip	red	44301

CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!
800.241.8334 | www.itwprobrands.com
LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved