



High Purity TXP

Laboratory-Certified Low Chloride Ink

HANDLING

- Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.



STORAGE

- Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

- Dispose of contents/container in accordance with local/regional/national/international regulations.

FEATURES

- Stainless steel ball tip – no risk of tip wear even when writing on rough surfaces
- Easily writes through oil, grease and water
- Drying time: 25 - 30 minutes

PHYSICAL PROPERTIES

Appearance / Physical State	Liquid.
Odor	mild
Flash Point	89.0 - 108.0 °F (31.7 - 42.2 °C)
Boiling Point / Range	253 - 338 °F (120 - 170 °C)
VOC Content	29.10%, 374 g/L
Evaporation Rate	< 1 (BuAc = 1)
Vapor Density	> 1 (air = 1)
Prop 65 Warning	YES

AVAILABLE IN

Units/Case	Marker Tip	Color	Part #
48	medium, steel	White	17463



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved