



# High Temp Marker

## HANDLING

- Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-pro

## STORAGE

- Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a

## DISPOSAL INFORMATION

- Dispose of contents/container in accordance with local/regional/national/international regulations.

## FEATURES

- Fiber tip paint marker with valve-action
- Valve-action mechanism prevents paint in barrel from drying when cap is left off
- Threaded barrel allows marker to be screwed into a jig or apparatus
- Drying time: 45 seconds - 1 minute



## PHYSICAL PROPERTIES

Physical State	Liquid.
Prop 65 Warning	YES
Temperature Range	2000°F (1093°C)

## AVAILABLE IN

Units/Case	Marker Tip	Color	Part #
12	Medium	White	44219
12	Medium	Yellow	44424
21	Medium	Black	44250
12	Medium	Green	44266
12	Medium	Blue	44094



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved