



Instant Super Degreaser 2.0



FEATURES

- Non-flammable – can be used on or near energized equipment. This improves safety and reduces downtime associated with de-energizing equipment.
- Non-brominated – improved health and safety profile for increased worker safety and simplified employer compliance.
- Fast Evaporation – quickens clean-up time. Improves productivity and reduces downtime
- No Rinsing/No Residue – no wiping or rinsing prior to next production step, reduces time and labor.
- Heavy-duty Performance – removes oil, grease, dirt, and tar with less cleaner, saving money.
- Non-conductive – can be used on or near energized equipment, eliminating equipment downtime.
- Power Blast Spray – blasts away dirt, oil, and other residues for quicker cleaning (increased productivity).

APPLICATIONS

- Air Compressors
- Bearings
- Cables
- Chains
- Forklifts
- Gears
- Heavy Equipment
- Power Tools

SPECIFICATIONS AND APPROVALS

- Airbus UK-ABR 9-0140; Issue 6 Type I
- Boeing D6-17457, Revision T
- NSF International, K1 (Aerosol)

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
07220	C07220	20 wt oz / 567 g / 437 mL	aerosol	12	19 lbs
07255	C07255	55 gal / 208 L	drum	1	369 lbs

PROPERTIES

Appearance/physical state	Gas/Aerosol
Odor	Mild
Melting point/freezing point	Not available
Boiling point/range	118°F (47.78°C)
Vapor pressure	> 300 mm Hg @ 25°C
Partition coefficient	Not available
Percent volatile	100%
Flammability limit	Not available
Propellant	Carbon dioxide
VOC Content	Aerosol - 77.2% per US Federal Consumer Product Regulations; Bulk - 84% per US Federal Consumer Product Regulations
Color	Colourless
Flash point	None - Tag Closed Cup
Density	11.00 lb/gallon
Evaporation rate	Not applicable
Vapor density	> 1 (air = 1)
Auto-ignition temperature	Not available
Viscosity	Not applicable
Relative Density	1.319
Temperature Range °F(°C)	Not applicable
4-Ball Weld Load	Not applicable

DIRECTIONS

Aerosol - Spray on parts and equipment. Bulk - Use in dip or spray applications. Allow flushing action to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. (see Section 7 of the SDS)

STORAGE

Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. (see Section 7 of the SDS)

DISPOSAL INFORMATION

Aerosol - Contents under pressure. Do not puncture, incinerate or crush. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved