

Accu-Lube® JL-12 Lubricant

FEATURES

- Easy to clean
- Gel formulation for no drip application - lowers amount of lubricant used/wasted
- Eliminates spilled/sprayed fluids
- Weldable with low smoke
- No build-up or residue
- Clean alternative to liquid lubricants
- Petroleum and pigment free

APPLICATIONS

- Metalforming Lubricant Gel

HANDLING

Avoid contact with skin, eyes, clothing. Wash thoroughly after handling.

STORAGE

Keep container tightly closed in a dry and well-ventilated place.

DISPOSAL

This material, as supplied, is not a hazardous waste according to Federal regulations (40CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to thi



PHYSICAL PROPERTIES

Appearance / Physical State	Gel
Color	Colorless, transparent
Odor	Mild
pH Value	7.5-8.5
Specific Gravity	0.95
Boiling Point / Range	100 °C - 212 °F
Vapor Pressure	<1 mmHg
Vapor Density	> 1
Prop 65 Warning	YES

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case
JL1205	5 gal	pail	1
JL1255	55 gal	drum	1



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved