

Accu-Lube® LB-1000

General Purpose MQL

FEATURES

- Heavy-duty machining, sawing and cutting
- Difficult steel & hardened metal operations
- Large diameter tapping
- Deep hole drilling
- High heat operations
- Sawing large diameter solids

APPLICATIONS

- Heavy-duty machining, sawing and cutting
- Difficult steel & hardened metal operations
- Large diameter tapping
- Deep hole drilling
- High heat operations
- Sawing large diameter solids

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

STORAGE

Keep container tightly closed.

DISPOSAL INFORMATION

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). Consult the appropriate state, regional, or local regulations for additional requirements.



PHYSICAL PROPERTIES

Appearance/physical state	Liquid
Odor	Mild
Melting point/freezing point	No data available
Boiling point/range	> 400°F/ > 204°C
Vapor pressure	< 1 mmHg
Partition coefficient	No data available
Percent volatile	No data available
Flammability limit	No data available
Propellant	N/A
VOC Content	None
Color	Blue
Flash point	> 400°F/ > 204°C
Relative density	No data available
Evaporation rate	No data available
Vapor density	> 1
Auto-ignition temperature	No data available
Viscosity	No data available
Specific Gravity (water=1)	0.93
Temperature Range °F(°C)	No data available
4-Ball Weld Load	No data available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
LB1000	1 gal	bottle	4	34 lbs
LB1055	55 gal	drum	1	459 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved