

Accu-Lube® LB-1000

General Purpose MQL

FEATURES

- Heavy-duty machining, sawing and cutting
- Difficult steel & hardened metal operations
- Large diameter tapping
- Deep hole drilling
- High heat operations
- Sawing large diameter solids

APPLICATIONS

- Heavy-duty machining, sawing and cutting
- Difficult steel & hardened metal operations
- Large diameter tapping
- Deep hole drilling
- High heat operations
- Sawing large diameter solids

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

STORAGE

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Dispose in accordance with all applicable regulations.



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Color	Blue
Odor	Mild
Boiling Point / Range	>399.2°F (>204.0°C)
Flash Point	>399.2°F (>204.0°C)
Pour Point	5°F (-15°C)
VOC Content	0.01 % , 0.14 g/l per US State and Federal Consumer Product Regulations
Specific Gravity	0.93
Viscosity	39 cSt @ 40°C

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LB1000	1 gal	bottle	4	34 lbs
LB1055	55 gal	drum	1	459 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved