

# **FEATURES**

- Heavy-duty machining, sawing and cutting
- Exotic and high nickel alloys
- Aerospace industry
- Large diameter tapping
- Deep hole drilling
- Carbide die stamping
- Sawing large diameter solids

### **APPLICATIONS**

- · Heavy duty machining
- Sawing

- Cutting
- Tapping

#### **DIRECTIONS**

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

### **HANDLING**

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

### **STORAGE**

Keep containers tightly closed in a dry, cool and well-ventilated place.

### **DISPOSAL INFORMATION**

This material, as supplied, is not a hazardous waste according to Federal regulations (40CFR 261). This material could become a hazardous waste if it is mixed with or otherwisecomes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.



# PHYSICAL PROPERTIES

Appearance/physical state	Liquid		
Odor	Mild		
Melting point/freezing point	No data available		
Boiling point/range	>204°C		
Vapor pressure	No data available		
Partition coefficient	No data available		
Percent volatile	No data available		
Flammability limit	No data available		
Propellant	N/A		
VOC Content	1.47 g/l		
Color	Blue		
Flash point	>204°C		
Relative density	No data available		
Evaporation rate	No data available		
Vapor density	No data available		
Auto-ignition temperature	No data available		
Viscosity	No data available		
Specific Gravity (water=1)	0.94		
Temperature Range °F(°C)	No data available		
4-Ball Weld Load	No data available		

# **AVAILABLE PRODUCTS**

Part No.	Net Contents	Container Type	Units/Case	Case Weight
LB1100	1 gal	bottle	4	34 lbs
LB1155	55 gal	drum	1	459 lbs

