

# Accu-Lube® LB-2000

## General Purpose MQL

### FEATURES

- General purpose near-dry machining lubricant
- Moderate to heavy-duty applications

### APPLICATIONS

- General machining, sawing and cutting
- Large diameter tapping
- Drilling & tapping small holes
- Broaching & spline rolling
- Sawing large diameter solids

### DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

### HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

### STORAGE

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

### DISPOSAL

Dispose in accordance with all applicable regulations.



### PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Color	Blue
Odor	Mild
Boiling Point / Range	>399.2°F (>204.0°C)
Flash Point	> 399.2 °F (> 204.0 °C)
Pour Point	-4°F (-20°C)
Vapor Pressure	< 1 mm Hg
Vapor density	>1
Water Solubility	Insoluble.
Specific Gravity	0.92
VOC Content	0.2 g/l
Viscosity	37 cSt @ 40°C

### AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LB2000	1 gal	bottle	4	34 lbs
LB2055	55 gal	drum	1	454 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved