

Accu-Lube® LB-3000

General Purpose MQL

APPLICATIONS

- General machining and sawing
- Replacement for "mist" type lubricant and coolant
- Lumber & wood cutting applications
- Moderate-duty
- Vegetable-based, biodegradable lubricant
- For ferrous & nonferrous metals, aluminum and titanium
- Clean before heat treating with soap and water

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

STORAGE

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Dispose of in accordance with local regulations.



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Color	Blue
Odor	Mild
Boiling Point / Range	>399.2°F (>204°C)
Flash Point	608°F (320°C)
Pour Point	-4°F (-20°C)
Vapor Pressure	<1 mm Hg
Vapor density	>1
Water Solubility	Insoluble.
Specific Gravity	0.92
VOC Content	0.2 g/l
Viscosity	37 cSt @ 40°C

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LB3000	1 gal	bottle	4	34 lbs
LB3055	55 gal	drum	1	454 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved