

Accu-Lube® LB-4600

Light Viscosity MQL

FEATURES

- Economical, light-duty minimum quantity lubricant
- Light-duty machining, sawing and cutting
- Aluminum extrusion machining and sawing
- Vegetable-based, biodegradable lubricant
- Non-staining, burns off cleanly in post heat treating
- For ferrous & nonferrous metals, aluminum and titanium
- Clean with soap and water

APPLICATIONS

- Light-duty machining, sawing and cutting
- Aluminum extrusion machining and sawing

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

None required under normal usage.

STORAGE

Keep containers tightly closed in a dry, cool and well-ventilated place.

DISPOSAL INFORMATION

Consult the appropriate state, regional, or local regulations for additional requirements.



PHYSICAL PROPERTIES

Appearance/physical state	Liquid
Odor	Mild
Melting point/freezing point	No data available
Boiling point/range	>150°C
Vapor pressure	No data available
Partition coefficient	No data available
Percent volatile	No data available
Flammability limit	No data available
Propellant	N/A
VOC Content	5.91 g/l
Color	Purple
Flash point	>150°C
Relative density	No data available
Evaporation rate	No data available
Vapor density	No data available
Auto-ignition temperature	No data available
Viscosity	No data available
Specific Gravity (water=1)	0.86
Temperature Range °F(°C)	No data available
4-Ball Weld Load	No data available

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
LB4600	1 gal.	Jug	4	34 lbs.
LB4655	55 gal.	Drum	1	454 lbs.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved